BARFORD SITE DUMPERS SX6000 IVECO N45MSSX00 (2007 AND AFTER)



ENGINE Iveco N45 MSSX00		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Agridiesel CRD+ 15W-40		
Change every 300 hours		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP Ultra 10W-40	Agrisynth LSP 10W-40	Armado Synth LSP Ultra 10W-40

Change every 300 hours

DIFFERENTIAL FRONT		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
Change every 600 hours		- ·

DIFFERENTIAL REAR		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
01 0001		

Change every 600 hours

TRANSFERBOX O&S	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
ATF-F (Ford)	
Change every 1200 hours/ 12 months	

Change every 1200 hours/ 12 months

BARFORD SITE DUMPERS SX6000 IVECO N45MSSX00 (2007 AND AFTER)



TRANSMISSION PowerShuttle/ITL	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
ATF-F (Ford)	
Change every 1200 hours/ 12 months	

Change every 1200 hours/ 12 months

HYDRAULIC SYSTEM		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus H 32	Perlus AF 32	
Ok		

Change every 1200 hours/ 12 months

CLIMATE
Moderate

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

COOLING SYSTEM		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Coolant -38 Organic NF		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.