

ENGINE Cummins 4BTA3.9C		
JSE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SCD 40	Multifleet SCD 30	
Change every 250 hours/ 6 months		,
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Kroontrak MTH 10W-30	Asyntho 5W-30
Change every 250 hours/ 6 months		
USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		
Change every 250 hours/ 6 months		
USE		CLIMATE
Initial service		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SCD 40	Multifleet SCD 30	
Change every 100 hours		
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Kroontrak MTH 10W-30	Asyntho 5W-30
Change every 100 hours		
USE		CLIMATE
Initial service		Cold
PRODUCT RECOMMENDATION 1  Multifleet SCD 10W		



<b>DIFFERENTIAL FRONT</b> Bell 14T		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	
Check every 250 hours, change every 500	hours	
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

DIFFERENTIAL REAR (TANDEM BOGIE) Clark-Hurth		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Unigear HS GL-3/GL-5 80W-90		
Check every 250 hours, change every 1000 hours		

FINAL DRIVES FRONT

USE CLIMATE

Normal Moderate

PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2

Gearlube GL-5 85W-140 Unigear LS GL-3/GL-5 85W-140

Change every 500 hours

Change every 100 hours

USE CLIMATE
Initial service Moderate
PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2

Gearlube GL-5 85W-140 Unigear LS GL-3/GL-5 85W-140

Change every 100 hours

HUB REDUCTIONS REAR (TANDEM BOGIE)		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Unigear HS GL-3/GL-5 80W-90		
Check every 250 hours, change every 2000 hours		



TRANSMISSION Clark 18000 3/3		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Multifleet SCD 30		
Check every 250 hours, change every	1000 hours	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SCD 10W	ATF Dexron II-D	
Check every 250 hours, change every	1000 hours	
USE		CLIMATE
Initial service		Mediterranean
PRODUCT RECOMMENDATION 1		
Multifleet SCD 30		
Change every 100 hours		
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SCD 10W	ATF Dexron II-D	
Change every 100 hours		

PRODUCT RECOMMENDATION 1		
·	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Normal		Moderate
JSE		CLIMATE
Perlus H 46	Perlus H 68	Perlus AF 46
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Normal		Mediterranean
ISE		CLIMATE
SE		CLIMATE

Labora Grease	Q5 WF Calcep Grease EF 2	Wir Littlep Grease Er 2
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Normal		Moderate
USE		CLIMATE
GREASE POINTS/NIPPLES		



COOLING SYSTEM		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	
Change every 2000 hours		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.