

BELL EQUIPMENT WHEELED LOADERS L L1706E JOHN DEERE POWERTECH PLUS 6068H (TIER 2/3)



ENGINE John Deere PowerTech Plus 6068H
Capacity: 19 liter

USE	CLIMATE
Normal, fuel sulfur level < 0,1 %	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP Ultra FE 5W-30	Agrisynth LSP Ultra 10W-40	Agrisynth LSP 10W-40

Change every 500 hours

DIFFERENTIAL FRONT
Capacity: 22 liter (Front)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid Synth XHP Ultra	Agrifluid HT-Plus	Kroontrak MTH 10W-30

Change every 1000 hours

DIFFERENTIAL REAR
Capacity: 17 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid Synth XHP Ultra	Agrifluid HT-Plus	Kroontrak MTH 10W-30

Change every 1000 hours

TRANSMISSION POWERSHIFT 4/3
Capacity: 22 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid Synth XHP Ultra	Agrifluid HT-Plus	Kroontrak MTH 10W-30

Change every 1000 hours

HYDRAULIC SYSTEM
Capacity: 110 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP Ultra FE 5W-30	Agrisynth LSP Ultra 10W-40	Agrisynth LSP 10W-40

Change every 4000 hours

BELL EQUIPMENT WHEELED LOADERS L L1706E JOHN DEERE POWERTECH PLUS 6068H (TIER 2/3)



GREASE POINTS/NIPPLES

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

MoS2 Grease EP 2

COOLING SYSTEM

Capacity: 27,4 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 15+

PRODUCT RECOMMENDATION 2

Coolant SP 12

PRODUCT RECOMMENDATION 3

Coolant -38 Organic NF*Change every 4000 hours*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.