PRODUCT RECOMMENDATION

BELL EQUIPMENT BACKHOE LOADERS 310G (4X4) JOHN DEERE 4045T

ENGINE John Deere PowerTech 4045T Capacity: 13 liter		
USE Normal		CLIMATE Moderate
PRODUCT RECOMMENDATION 1 **Agrisynth LSP Ultra 10W-40**	PRODUCT RECOMMENDATION 2 **Agrisynth LSP 10W-40**	PRODUCT RECOMMENDATION 3 **Agridiesel CRD+ 15W-40**
Change every 500 hours		

DIFFERENTIAL FRONT Capacity: 6,5 liter		
USE Normal		CLIMATE Moderate
PRODUCT RECOMMENDATION 1 **Agrifluid Synth XHP Ultra**	PRODUCT RECOMMENDATION 2 **Agrifluid HT-Plus**	PRODUCT RECOMMENDATION 3 **Kroontrak MTH 10W-30**
Change every 1000 hours		

DIFFERENTIAL REAR Capacity: 16 liter		
USE Normal		CLIMATE Moderate
PRODUCT RECOMMENDATION 1 **Agrifluid Synth XHP Ultra**	PRODUCT RECOMMENDATION 2 **Agrifluid HT-Plus**	PRODUCT RECOMMENDATION 3 **Kroontrak MTH 10W-30**
Change every 1000 hours		

HUB REDUCTIONS FRONT Capacity: 1 liter (each hub)		
USE Normal		CLIMATE Moderate
PRODUCT RECOMMENDATION 1 **Agrifluid Synth XHP Ultra**	PRODUCT RECOMMENDATION 2 **Agrifluid HT-Plus**	PRODUCT RECOMMENDATION 3 **Kroontrak MTH 10W-30**
Change every 1000 hours		

TRANSMISSION POWERSHIFT 4/4 Capacity: 15 liter (+ torque converter)		
USE Normal		CLIMATE Moderate
PRODUCT RECOMMENDATION 1 **Agrifluid Synth XHP Ultra**	PRODUCT RECOMMENDATION 2 **Agrifluid HT-Plus**	PRODUCT RECOMMENDATION 3 **Kroontrak MTH 10W-30**
Change every 1000 hours		

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

BELL EQUIPMENT BACKHOE LOADERS 310G (4X4) JOHN DEERE 4045T

HYDRAULIC SYSTEM
Capacity: 37 liter (Hydraulic tank)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP Ultra 10W-40	**Agrisynth LSP 10W-40**	**Agridiesel CRD+ 15W-40**

Change every 2000 hours

GREASE POINTS/NIPPLES

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		

COOLING SYSTEM
Capacity: 16 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	**Coolant SP 12**	**Coolant -38 Organic NF**

Change every 2000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367