

# BOBCAT TRACKED LOADERS T140 (2005-2009)



**ENGINE** Kubota V2203-M  
Capacity: 8,7 liter

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1  
**Multifleet SHPD 20W-50**

PRODUCT RECOMMENDATION 2  
**Multifleet SCD 40**

*Check every 10 hours, change every 250 hours/ 12 months*

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1  
**Multifleet SCD 30**

*Check every 10 hours, change every 250 hours/ 12 months*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1  
**Kroontrak MTH 10W-30**

PRODUCT RECOMMENDATION 2  
**Synfleet SHPD 10W-40**

PRODUCT RECOMMENDATION 3  
**Dieselfleet CD+ 15W-40**

*Check every 10 hours, change every 250 hours/ 12 months*

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1  
**Multifleet SCD 10W**

*Check every 10 hours, change every 250 hours/ 12 months*

USE	CLIMATE
Initial service	Tropical

PRODUCT RECOMMENDATION 1  
**Multifleet SHPD 20W-50**

PRODUCT RECOMMENDATION 2  
**Multifleet SCD 40**

*Check every 10 hours, change every 50 hours*

USE	CLIMATE
Initial service	Mediterranean

PRODUCT RECOMMENDATION 1  
**Multifleet SCD 30**

*Check every 10 hours, change every 50 hours*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1  
**Kroontrak MTH 10W-30**

PRODUCT RECOMMENDATION 2  
**Synfleet SHPD 10W-40**

PRODUCT RECOMMENDATION 3  
**Dieselfleet CD+ 15W-40**

*Check every 10 hours, change every 50 hours*

# BOBCAT TRACKED LOADERS T140 (2005-2009)



USE		CLIMATE
Initial service		Cold
PRODUCT RECOMMENDATION 1		
<b>Multifleet SCD 10W</b>		
<i>Check every 10 hours, change every 50 hours</i>		

HYDRAULIC SYSTEM HYDROSTATIC DRIVE		
Capacity: 13,3 liter (Hydraulic tank), Capacity: 22,7 liter (Total)		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
<b>Perlus AF 100</b>		
<i>Check every 50 hours, change every 1000 hours/ 12 months</i>		

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Perlus H 46</b>	<b>Perlus H 68</b>	<b>Perlus AF 46</b>
<i>Check every 50 hours, change every 1000 hours/ 12 months</i>		

USE		CLIMATE
Acceptable		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Kroontrak MTH 10W-30</b>	<b>HDX 10W</b>	
<i>Check every 50 hours, change every 1000 hours/ 12 months</i>		

USE		CLIMATE
Biodegradable oil		Moderate
PRODUCT RECOMMENDATION 1		
<b>Perlus Biosynth 46</b>		
<i>Check every 50 hours, change every 1000 hours/ 12 months</i>		

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>
<i>Change every 10 hours</i>		



# BOBCAT TRACKED LOADERS T140 (2005-2009)



## COOLING SYSTEM

Capacity: 11,4 liter, Capacity: 11,9 liter (with 4 zone airconditioning system)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant -38 Organic NF</b>	<b>Coolant -26</b>	

*Check every 10 hours, change every 24 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*