BOBCAT EXCAVATORS E08 KUBOTA D722- E2B(TIER 2) (2008-2017)



ENGINE Kubota D722-E2B Capacity: 3,5 liter		
USE		CLIMATE
Normal		Tropical
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SHPD 20W-50	Multifleet SCD 40	
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Multifleet SCD 30		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak MTH 10W-30	Synfleet SHPD 10W-40	Dieselfleet CD+ 15W-40
USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		

Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90			
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Normal		Moderate		
USE		CLIMATE		
TRAVEL REDUCTION UNIT SEPARATE LUBRICATION				

use Normal		climate Moderate
Perlus Biosynth 46	Perlus H 46	
USE		CLIMATE
Biodegradable oil		Moderate
PRODUCT RECOMMENDATION 1		
Perlus Biosynth 46		

BOBCAT EXCAVATORS E08 KUBOTA D722- E2B(TIER 2) (2008-2017)



COOLING SYSTEM Capacity: 3 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant -33 MPG	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.