PRODUCT RECOMMENDATION

# BOBCAT TELESCOPIC HANDLERS T40140 PERKINS 1104.44T (2004-2013)

**ENGINE** Perkins 1104-44T
Capacity: 8,5 liter

| USE | | CLIMATE |
|---|---|---|
| Normal | | Tropical |
| **PRODUCT RECOMMENDATION 1** | **PRODUCT RECOMMENDATION 2** | |
| **Multifleet SHPD 20W-50** | **Multifleet SCD 40** | |

*Check every 10 hours, change every 500 hours*

| USE | | CLIMATE |
|---|---|---|
| Normal | | Mediterranean |
| **PRODUCT RECOMMENDATION 1** | | |
| **Multifleet SCD 30** | | |

*Check every 10 hours, change every 500 hours*

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| **PRODUCT RECOMMENDATION 1** | **PRODUCT RECOMMENDATION 2** | **PRODUCT RECOMMENDATION 3** |
| **Kroontrak MTH 10W-30** | **Synfleet SHPD 10W-40** | **Dieselfleet CD+ 15W-40** |

*Check every 10 hours, change every 500 hours*

| USE | | CLIMATE |
|---|---|---|
| Normal | | Cold |
| **PRODUCT RECOMMENDATION 1** | | |
| **Multifleet SCD 10W** | | |

*Check every 10 hours, change every 500 hours*

**DIFFERENTIAL FRONT** Dana
Capacity: 6,7 liter

| USE | | CLIMATE |
|---|---|---|
| Normal | | Mediterranean |
| **PRODUCT RECOMMENDATION 1** | **PRODUCT RECOMMENDATION 2** | |
| **Gearlube GL-5 80W-90** | **Unigear HS GL-3/GL-5 80W-90** | |

*Check every 1 months/ 200 hours, change every 800 hours/ 12 months*

**DIFFERENTIAL REAR** Dana
Capacity: 6,6 liter

| USE | | CLIMATE |
|---|---|---|
| Normal | | Mediterranean |
| **PRODUCT RECOMMENDATION 1** | **PRODUCT RECOMMENDATION 2** | |
| **Gearlube GL-5 80W-90** | **Unigear HS GL-3/GL-5 80W-90** | |

*Check every 1 months/ 200 hours, change every 800 hours/ 12 months*

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

# BOBCAT TELESCOPIC HANDLERS T40140 PERKINS 1104.44T (2004-2013)

## HUB REDUCTIONS FRONT
Capacity: 0,8 liter

| USE | CLIMATE |
|---|---|
| Normal | Mediterranean |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|---|---|---|
| **Gearlube GL-5 80W-90** | **Unigear HS GL-3/GL-5 80W-90** | |

*Check every 200 hours, change every 1000 hours/ 12 months*

## HUB REDUCTIONS REAR
Capacity: 0,8 liter

| USE | CLIMATE |
|---|---|
| Normal | Mediterranean |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|---|---|---|
| **Gearlube GL-5 80W-90** | **Unigear HS GL-3/GL-5 80W-90** | |

*Check every 200 hours, change every 1000 hours/ 12 months*

## TRANSFERBOX
Capacity: 0,8 liter

| USE | CLIMATE |
|---|---|
| Normal | Mediterranean |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|---|---|---|
| **Gearlube GL-5 80W-90** | **Unigear HS GL-3/GL-5 80W-90** | |

*Check every 1 months/ 200 hours, change every 800 hours/ 12 months*

## HYDRAULIC SYSTEM
Capacity: 77 liter (Hydraulic tank), Capacity: 145 liter (Total)

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|---|---|---|
| **Perlus Biosynth 46** | **Perlus H 46** | |

*Check every 10 hours, change every 1000 hours/ 12 months*

## HYDRAULIC BRAKE SYSTEM

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|---|---|---|
| **Perlus Biosynth 46** | **Perlus H 46** | |

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

# BOBCAT TELESCOPIC HANDLERS T40140 PERKINS 1104.44T (2004-2013)

## GREASE POINTS/NIPPLES

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| **PRODUCT RECOMMENDATION 1** | **PRODUCT RECOMMENDATION 2** | **PRODUCT RECOMMENDATION 3** |
| **Labora Grease** | **Q5 MP Calcep Grease EP 2** | **MP Lithep Grease EP 2** |
| *Change every 50 hours* | | |

## COOLING SYSTEM
Capacity: 17 liter

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| **PRODUCT RECOMMENDATION 1** | **PRODUCT RECOMMENDATION 2** | |
| **Coolant -38 Organic NF** | **Coolant -26** | |
| *Check every 50 hours* | | |

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367