PRODUCT RECOMMENDATION

# CASE WHEELED LOADERS 721E XR CASE, 4. GEN., 667TA/EED, TIER-III (2007-2011)

## ENGINE Case 667TA/EED Tier 3
Capacity: 14,2 liter, Filter capacity: 1 liter

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|---|---|---|
| **Agridiesel CRD+ 15W-40** | **Dieselfleet CD+ 15W-40** | **Multifleet SHPD 15W-40** |

*Check every 10 hours, change every 500 hours*

| USE | CLIMATE |
|---|---|
| Initial service | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|---|---|---|
| **Agridiesel CRD+ 15W-40** | **Dieselfleet CD+ 15W-40** | **Multifleet SHPD 15W-40** |

*Check every 10 hours, change every 100 hours*

## DIFFERENTIAL FRONT
Capacity: 30,3 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

## DIFFERENTIAL REAR
Capacity: 23,7 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

## HUB REDUCTIONS FRONT

We are unable to give a standard recommendation for this component. Please contact our service department.

## HUB REDUCTIONS REAR

We are unable to give a standard recommendation for this component. Please contact our service department.

## TRANSMISSION 4F/3R Electronic 4/3
Capacity: 25,6 liter

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|---|---|---|
| **Agridiesel CRD+ 15W-40** | **Dieselfleet CD+ 15W-40** | **Multifleet SHPD 15W-40** |

*Check every 50 hours, change every 1000 hours*

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

# CASE WHEELED LOADERS 721E XR CASE, 4. GEN., 667TA/EED, TIER-III (2007-2011)

## HYDRAULIC SYSTEM
Capacity: 106 liter (Hydraulic tank), Capacity: 176 liter (Total)

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| **Agrifluid HT-Plus** | | |

*Check every 50 hours, change every 2000 hours*

## GREASE POINTS/NIPPLES

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| **MoS2 Grease EP 2** | | |

*Change every 100 hours*

## COOLING SYSTEM
Capacity: 36,9 liter

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| **Coolant -38 Organic NF** | **Coolant -26** | |

*Check every 50 hours, change every 2000 hours*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367