

CASE WHEELED LOADERS 821C CASE 6TAA-830 (1999-2006)



ENGINE Case 6TAA-8304
Capacity: 20,9 liter

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1

Multifleet SHPD 20W-50

Check every 10 hours, change every 250 hours

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Agridiesel CRD+ 15W-40

PRODUCT RECOMMENDATION 2

Dieselfleet CD+ 15W-40

PRODUCT RECOMMENDATION 3

Multifleet SHPD 15W-40

Check every 10 hours, change every 250 hours

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1

Kroontrak MTH 10W-30

PRODUCT RECOMMENDATION 2

Synfleet SHPD 10W-40

PRODUCT RECOMMENDATION 3

Dieselfleet LSP Ultra 10W-30

Check every 10 hours, change every 250 hours

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1

Asyntho 5W-30

PRODUCT RECOMMENDATION 2

Armado Synth 5W-30

Check every 10 hours, change every 250 hours

DIFFERENTIAL FRONT

Capacity: 1,9 liter (LS-additive), Capacity: 21 liter (Total)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Unigear LS GL-3/GL-5 85W-140

Change every 1000 hours

DIFFERENTIAL REAR

Capacity: 1,4 liter (LS-additive), Capacity: 15 liter (Total)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Unigear LS GL-3/GL-5 85W-140

Change every 1000 hours

CASE WHEELED LOADERS 821C CASE 6TAA-830 (1999-2006)



HUB REDUCTIONS

Capacity: 6,2 liter (Front), Capacity: 5,7 liter (Rear)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Unigear LS GL-3/GL-5 85W-140*Change every 1000 hours*

TRANSMISSION POWERSHIFT ZF 4/3

Capacity: 12,3 liter (Change capacity)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 2032

PRODUCT RECOMMENDATION 2

ATF Almirol*Check every 50 hours, change every 1000 hours*

USE	CLIMATE
First change only	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 2032

PRODUCT RECOMMENDATION 2

ATF Almirol*Check every 50 hours, change every 100 hours*

HYDRAULIC SYSTEM

Capacity: 90,1 liter (Hydraulic tank), Capacity: 174,2 liter (Total)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 2032

PRODUCT RECOMMENDATION 2

ATF Almirol*Check every 50 hours, change every 2000 hours*

GREASE POINTS/NIPPLES

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

MoS2 Grease EP 2*Check every 50 hours, change every 1000 hours*

CASE WHEELED LOADERS 821C CASE 6TAA-830 (1999-2006)

**COOLING SYSTEM**

Capacity: 34 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

Check every 10 hours, change every 2000 hours/ 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.