# **CASE WHEELED LOADERS 921C XR** CUMMINS QSM11 (1999-2008)



<b>ENGINE</b> Cummins QSM11 Capacity: 36,9 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40

Change every 250 hours

### DIFFERENTIAL FRONT

Capacity: 36,6 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

#### DIFFERENTIAL REAR Capacity: 36,3 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

### HUB REDUCTIONS

Capacity: 13,6 liter (each hub)

We are unable to give a standard recommendation for this component. Please contact our service department.

TRANSMISSION POWERSHIFT ZF 4/3 Capacity: 28,4 liter (Change capacity), Capacity: 46 liter (Dry fill)				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
SP Matic 2032	ATF Almirol			
Check every 50 hours, change every 1000 hours				

		3
SP Matic 2032	ATF Almirol	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
First change only		Moderate
USE		CLIMATE

Check every 50 hours, change every 100 hours

HYDRAULIC SYSTEM Capacity: 125 liter (Hydraulic tank), Capacity: 242 liter (Total)			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
Agrifluid HT-Plus			
Check every 50 hours, change every 2000 hours			

Check every 50 hours, change every 2000 hours

# CASE WHEELED LOADERS 921C XR CUMMINS QSM11 (1999-2008)



COOLING SYSTEM Capacity: 57 liter				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Coolant -38 Organic NF	Coolant -26			

Check every 10 hours, change every 2000 hours/ 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.