CASE WHEELED EXCAVATORS WX WX188 CASE F4GE9684E (2013-2021)



ENGINE FPT F4GE9684E Capacity: 15 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel MSP 15W-40	Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40

DIFFERENTIAL FRONT

Capacity: 9,5 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

DIFFERENTIAL REAR

Capacity: 12 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

HUB REDUCTIONS FRONT

Capacity: 2,4 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

HUB REDUCTIONS REAR

Capacity: 2,4 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

TRANSMISSION Powershift Capacity: 2,5 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Agridiesel MSP 15W-40	Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	

HYDRAULIC SYSTEM Capacity: 160 liter (Hydraulic tank), Capacity: 235 liter (System including tank (mono articulation)), Capacity: 250 liter (System including tank (triple articulation)) USE Normal PRODUCT RECOMMENDATION 1 Perlus H 68

CASE WHEELED EXCAVATORS WX WX188 CASE F4GE9684E (2013-2021)



GREASE POINTS/NIPPLES				
USE	CLIMATE			
Normal	Moderate			
PRODUCT RECOMMENDATION 1				
MoS2 Grease EP 2				

COOLING SYSTEM Capacity: 22 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant SP 15+	Coolant SP 12		

SWING REDUCTION UNIT Capacity: 3,5 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.