## CATERPILLAR ARTICULATED DUMP TRUCKS 725 AFX (TILL 2007)



| ENGINE<br>Capacity: 36 liter |                          |                          |
|------------------------------|--------------------------|--------------------------|
| USE                          |                          | CLIMATE                  |
| Normal                       |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1     | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agridiesel CRD+ 15W-40       | Synfleet SHPD 10W-40     | Dieselfleet CD+ 15W-40   |

Change every 250 hours

| DIFFERENTIAL CENTRE<br>Capacity: 45 liter |          |
|---|----------|
| USE                                       | CLIMATE  |
| Normal                                    | Moderate |
| PRODUCT RECOMMENDATION 1                  |          |
| Gear Oil Alcat 50                         |          |
| 01 1 5001 1 000                           | ·        |

Check every 500 hours, change every 2000 hours

| DIFFERENTIAL FRONT<br>Capacity: 41 liter |         |          |
|--|---------|----------|
| USE                                      |         | CLIMATE  |
| Normal                                   |         | Moderate |
| PRODUCT RECOMMENDATION 1                 |         |          |
| Gear Oil Alcat 50                        |         |          |
| Charle avery EOO hours abanga avery 200  | 0 houro |          |

Check every 500 hours, change every 2000 hours

| DIFFERENTIAL REAR<br>Capacity: 48 liter |          |
|---|----------|
| USE                                     | CLIMATE  |
| Normal                                  | Moderate |
| PRODUCT RECOMMENDATION 1                |          |
| Gear Oil Alcat 50                       |          |
|   |          |

Check every 500 hours, change every 2000 hours

| FINAL DRIVES<br>Capacity: 5 liter      |          |          |
|--|----------|----------|
| USE                                    |          | CLIMATE  |
| Normal (preferred)                     |          | Moderate |
| PRODUCT RECOMMENDATION 1               |          |          |
| Gear Oil Alcat 50                      |          |          |
| Check every 500 hours, change every 20 | 00 hours |          |

ery

## CATERPILLAR ARTICULATED DUMP TRUCKS 725 AFX (TILL 2007)



| TRANSFERBOX<br>Capacity: 18 liter              |          |               |
|--|----------|---------------|
| USE  |          | CLIMATE       |
| Normal   |          | Mediterranean |
| PRODUCT RECOMMENDATION 1                       |          |               |
| Gear Oil Alcat 30                              |          |               |
| Check every 500 hours, change every 1000 hours |          |               |
| USE  |          | CLIMATE       |
| Normal   |          | Cold          |
| PRODUCT RECOMMENDATION 1                       |          |               |
| Gear Oil Alcat 10W                             |          |               |
| Chack over 500 hours chapped over 100          | 10 hours |               |

Check every 500 hours, change every 1000 hours

| TRANSMISSION + TORQUE CONVERTER<br>Capacity: 36 liter |  |               |
|---|--|---------------|
| USE   |  | CLIMATE       |
| Normal  |  | Mediterranean |
| PRODUCT RECOMMENDATION 1                              |  |               |
| Gear Oil Alcat 30                                     |  |               |
|   |  | :             |

Check every 500 hours, change every 1000 hours

| USE  |  | CLIMATE |
|--|--|---------|
| Normal   |  | Cold    |
| PRODUCT RECOMMENDATION 1                       |  |         |
| Gear Oil Alcat 10W                             |  |         |
| Check avery 500 hours, change avery 1000 hours |  |         |

Check every 500 hours, change every 1000 hours

| COOLING SYSTEM<br>Capacity: 67 liter      |                    |
|---|--------------------|
| use<br>Normal                             | сымате<br>Moderate |
| PRODUCT RECOMMENDATION 1<br>Coolant SP 17 |                    |

## CATERPILLAR ARTICULATED DUMP TRUCKS 725 AFX (TILL 2007)



| HYDRAULIC SYSTEM STEERING + BRA<br>Capacity: 151 liter | KES |          |
|--|-----|----------|
| USE  |     | CLIMATE  |
| Normal   |     | Moderate |
| PRODUCT RECOMMENDATION 1                               |     |          |
| Gear Oil Alcat 10W                                     |     |          |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.