CATERPILLAR RIGID DUMP TRUCKS 773F EED (2006-2012)



ENGINE C27 Acert Capacity: 95 liter			
USE		CLIMATE	
Preferred		Mediterranean	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Agridiesel MSP 15W-40	Dieselfleet MSP 15W-40		

Check every 10 hours, change every 3 months/ 500 hours

USE		CLIMATE
Preferred		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP Ultra FE 5W-30	Agrisynth LSP Ultra 10W-40	Agrisynth MSP 10W-40

Check every 10 hours, change every 3 months/ 500 hours

USE	CLIMATE
Alternative (acceptable)	Mediterranean
PRODUCT RECOMMENDATION 1	
Dieselfleet MSP 15W-40	

Check every 10 hours, change every 3 months/ 500 hours

USE		CLIMATE
Alternative (acceptable)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP Ultra FE 5W-30	Agrisynth LSP Ultra 10W-40	Agrisynth MSP 10W-40

Check every 10 hours, change every 3 months/ 500 hours

USE		CLIMATE
Acceptable		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40

Check every 10 hours, change every 3 months/ 500 hours

Agrisynth LSP 10W-40	Multifleet SHPD 10W-40	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Acceptable		Moderate
USE		CLIMATE

Check every 10 hours, change every 3 months/ 500 hours

DIFFERENTIAL REAR

Capacity: 151 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

CATERPILLAR RIGID DUMP TRUCKS 773F EED (2006-2012)



USE		CLIMATE
Flexible (max)		Mediterranean
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		
Check every 10 hours, change ever	y 6 months/ 1000 hours	·
USE		CLIMATE
Flexible (max)		Cold
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		
Check every 10 hours, change ever	y 6 months/ 1000 hours	

HYDRAULIC SYSTEM HOIST + BRAKE Capacity: 130 liter (Hydraulic tank)		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		
0, 1, 10, 1, 0, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1,	4000 /	

Check every 10 hours, change every 6 months/ 1000 hours

CENTRAL LUBRICATION SYSTEM

We are unable to give a standard recommendation for this component. Please contact our service department.

FAN DRIVE BEARINGS

We are unable to give a standard recommendation for this component. Please contact our service department.

USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
MoS2 Grease EP 2	
JSE	CLIMATE
Light Duty	Moderate
PRODUCT RECOMMENDATION 1	
T KODOCT KECOMMENDATION I	

PRODUCT RECOMMENDATION

CATERPILLAR RIGID DUMP TRUCKS 773F EED (2006-2012)



WHEEL BEARINGS FRONT

Capacity: 3,4 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

COOLING SYSTEM Capacity: 174 liter		
USE		CLIMATE
Extended		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 17		
Check every 10 hours, change every	36 months/ 6000 hours	•

POWER STEERING HYDRAULIC SYSTEM Capacity: 38 liter (Hydraulic tank)		
use Normal	climate Mediterranean	
PRODUCT RECOMMENDATION 1 Gear Oil Alcat 30		

Check every 10 hours, change every 6 months/ 1000 hours

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Agrifluid HT-Plus	Kroontrak MTH 10W-30
Agridiesel CRD+ 15W-40	Agrifluid HT-Plus	Kroontrak MTH 10W-30

Check every 10 hours, change every 6 months/ 1000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.