

CATERPILLAR SKID STEER LOADERS

262C CATERPILLAR C3.4 DIT (2008-2011)



ENGINE C3.4 DIT
Capacity: 10 liter, Filter capacity: 1 liter

USE
Normal

CLIMATE
Mediterranean

PRODUCT RECOMMENDATION 1
Agridiesel CRD+ 15W-40

PRODUCT RECOMMENDATION 2
Dieselfleet CD+ 15W-40

PRODUCT RECOMMENDATION 3
Multifleet SHPD 15W-40

Check every 250 hours, change every 500 hours/ 12 months

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Agrisynth LSP 10W-40

PRODUCT RECOMMENDATION 2
Multifleet SHPD 10W-40

Check every 250 hours, change every 500 hours/ 12 months

HYDRAULIC SYSTEM HYDROSTATIC DRIVE
Capacity: 39 liter (Hydraulic tank)

USE
Preferred

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Gear Oil Alcat 10W

Check every 10 hours, change every 2000 hours/ 12 months

USE
Normal

CLIMATE
Mediterranean

PRODUCT RECOMMENDATION 1
Gear Oil Alcat 30

Check every 10 hours, change every 2000 hours/ 12 months

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Gear Oil Alcat 10W

Check every 10 hours, change every 2000 hours/ 12 months

USE
Alternative (acceptable)

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Agridiesel CRD+ 15W-40

PRODUCT RECOMMENDATION 2
Dieselfleet CD+ 15W-40

PRODUCT RECOMMENDATION 3
Multifleet SHPD 15W-40

Check every 10 hours, change every 2000 hours/ 12 months

CATERPILLAR SKID STEER LOADERS

262C CATERPILLAR C3.4 DIT (2008-2011)



USE		CLIMATE
Biodegradable oil		Moderate
PRODUCT RECOMMENDATION 1		
Perlus Biosynth 46		
<i>Check every 10 hours, change every 2000 hours/ 12 months</i>		

EXTERNAL GREASE POINTS

We are unable to give a standard recommendation for this component. Please contact our service department.

COOLING SYSTEM Capacity: 13,9 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 17		
<i>Change every 12000 hours/ 72 months</i>		

DRIVE CHAIN CASE Capacity: 10 liter		
USE		CLIMATE
Preferred		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40
<i>Check every 3 months/ 500 hours, change every 6 months/ 1000 hours</i>		
USE		CLIMATE
Preferred		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agrisynth LSP 10W-40	Multifleet SHPD 10W-40	
<i>Check every 3 months/ 500 hours, change every 6 months/ 1000 hours</i>		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.