

CATERPILLAR WHEELED LOADERS 938K

SWL (2012 AND AFTER)



ENGINE C6.6 Acert
Capacity: 19,5 liter

USE
Normal

CLIMATE
Mediterranean

PRODUCT RECOMMENDATION 1
Agrisynth MSP 10W-40

PRODUCT RECOMMENDATION 2
Dieselfleet MSP 15W-40

Check every 10 hours, change every 500 hours

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Agrisynth LSP Ultra FE 5W-30

PRODUCT RECOMMENDATION 2
Agridiesel MSP 15W-40

PRODUCT RECOMMENDATION 3
Dieselfleet LSP Ultra 10W-30

Check every 10 hours, change every 500 hours

DIFFERENTIAL FRONT
Capacity: 35 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Agrifluid HT-Plus

PRODUCT RECOMMENDATION 2
Kroontrak MTH 10W-30

PRODUCT RECOMMENDATION 3
Agrifluid HT

Check every 250 hours, change every 2000 hours

DIFFERENTIAL REAR
Capacity: 35 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Agrifluid HT-Plus

PRODUCT RECOMMENDATION 2
Kroontrak MTH 10W-30

PRODUCT RECOMMENDATION 3
Agrifluid HT

Check every 250 hours, change every 2000 hours

CATERPILLAR WHEELED LOADERS 938K

SWL (2012 AND AFTER)



TRANSMISSION

Capacity: 11 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gear Oil Alcat 30	Gear Oil Alcat 50	

Check every 10 hours, change every 2000 hours

USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		

Check every 10 hours, change every 2000 hours

HYDRAULIC SYSTEM

Capacity: 90 liter (Hydraulic tank)

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		

Check every 10 hours, change every 2000 hours

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth MSP 10W-40	Agrifluid HT-Plus	Kroontrak MTH 10W-30

Check every 10 hours, change every 2000 hours

USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Agridiesel MSP 15W-40		

Check every 10 hours, change every 2000 hours

USE		CLIMATE
Biodegradable oil		Moderate
PRODUCT RECOMMENDATION 1		
Perlus Biosynth 46		

Check every 10 hours, change every 2000 hours

CATERPILLAR WHEELED LOADERS 938K

SWL (2012 AND AFTER)



GREASE POINTS/NIPPLES

USE

Alternative (acceptable)

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

MoS2 Grease EP 2

COOLING SYSTEM

Capacity: 32 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 17

Check every 10 hours, change every 72 months/ 12000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.