

# CATERPILLAR WHEELED LOADERS 982M N8T (2014 AND AFTER)



**ENGINE** C13 Acert  
Capacity: 37 liter

USE	CLIMATE
Preferred	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
<b>Agridiesel MSP 15W-40</b>	<b>Dieselfleet MSP 15W-40</b>

*Check every 10 hours, change every 3 months/ 500 hours*

USE	CLIMATE
Preferred	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Armado Synth MSP 5W-40</b>	<b>Dieselfleet LSP Ultra 10W-30</b>	<b>Dieselfleet MSP 10W-30</b>

*Check every 10 hours, change every 3 months/ 500 hours*

USE	CLIMATE
Initial service	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
<b>Agridiesel MSP 15W-40</b>	<b>Dieselfleet MSP 15W-40</b>

*Change every 250 hours/ 6 months*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Armado Synth MSP 5W-40</b>	<b>Dieselfleet LSP Ultra 10W-30</b>	<b>Dieselfleet MSP 10W-30</b>

*Change every 250 hours/ 6 months*

USE	CLIMATE
Alternative (acceptable)	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
<b>Agrisynth MSP 10W-40</b>	<b>Dieselfleet MSP 15W-40</b>

*Check every 10 hours, change every 3 months/ 500 hours*

USE	CLIMATE
Alternative (acceptable)	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agrisynth LSP Ultra 10W-40</b>	<b>Agridiesel MSP 15W-40</b>	<b>Armado Synth LSP Ultra 10W-40</b>

*Check every 10 hours, change every 3 months/ 500 hours*

USE	CLIMATE
Initial service (alternative)	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
<b>Agrisynth MSP 10W-40</b>	<b>Dieselfleet MSP 15W-40</b>

*Change every 250 hours/ 6 months*

# CATERPILLAR WHEELED LOADERS 982M N8T (2014 AND AFTER)



USE		CLIMATE
Initial service (alternative)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agrisynth LSP Ultra 10W-40</b>	<b>Agridiesel MSP 15W-40</b>	<b>Armado Synth LSP Ultra 10W-40</b>
<i>Change every 250 hours/ 6 months</i>		

## DIFFERENTIAL FRONT

Capacity: 84 liter (+ hub reductions), Capacity: 1,5 liter (special additive)

We are unable to give a standard recommendation for this component. Please contact our service department.

## DIFFERENTIAL REAR

Capacity: 84 liter (+ hub reductions), Capacity: 1,5 liter (special additive)

We are unable to give a standard recommendation for this component. Please contact our service department.

## HUB REDUCTIONS FRONT

We are unable to give a standard recommendation for this component. Please contact our service department.

## HUB REDUCTIONS REAR

We are unable to give a standard recommendation for this component. Please contact our service department.

# CATERPILLAR WHEELED LOADERS 982M N8T (2014 AND AFTER)



**TRANSMISSION** Powershift  
Capacity: 77 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gear Oil Alcat 30</b>	<b>Gear Oil Alcat 50</b>	

*Check every 10 hours, change every 6 months/ 1000 hours*

USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		
<b>Gear Oil Alcat 10W</b>		

*Check every 10 hours, change every 6 months/ 1000 hours*

USE		CLIMATE
Fluid analysis		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gear Oil Alcat 30</b>	<b>Gear Oil Alcat 50</b>	

*Check every 3 months/ 500 hours*

USE		CLIMATE
Fluid analysis		Cold
PRODUCT RECOMMENDATION 1		
<b>Gear Oil Alcat 10W</b>		

*Check every 3 months/ 500 hours*

## HYDRAULIC SYSTEM 2 VALVE TYPE

Capacity: 280 liter (Complete), Capacity: 163 liter (Hydraulic tank)

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
<b>Gear Oil Alcat 30</b>		

*Check every 10 hours, change every 3000 hours*

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agrisynth LSP Ultra 10W-40</b>	<b>Agrisynth MSP 10W-40</b>	<b>Agrifluid HT-Plus</b>

*Check every 10 hours, change every 3000 hours*

# CATERPILLAR WHEELED LOADERS 982M N8T (2014 AND AFTER)



USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
<b>Agridiesel MSP 15W-40</b>		
<i>Check every 10 hours, change every 3000 hours</i>		
USE		CLIMATE
Fluid analysis		Mediterranean
PRODUCT RECOMMENDATION 1		
<b>Gear Oil Alcat 30</b>		
<i>Check every 500 hours</i>		
USE		CLIMATE
Fluid analysis		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agrisynth LSP Ultra 10W-40</b>	<b>Agrisynth MSP 10W-40</b>	<b>Agrifluid HT-Plus</b>
<i>Check every 500 hours</i>		
USE		CLIMATE
Fluid analysis		Arctic
PRODUCT RECOMMENDATION 1		
<b>Agridiesel MSP 15W-40</b>		
<i>Check every 500 hours</i>		
HYDRAULIC SYSTEM 3 VALVE TYPE		
Capacity: 283 liter (Complete), Capacity: 163 liter (Hydraulic tank)		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
<b>Gear Oil Alcat 30</b>		
<i>Check every 10 hours, change every 3000 hours</i>		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agrisynth LSP Ultra 10W-40</b>	<b>Agrisynth MSP 10W-40</b>	<b>Agrifluid HT-Plus</b>
<i>Check every 10 hours, change every 3000 hours</i>		
USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
<b>Agridiesel MSP 15W-40</b>		
<i>Check every 10 hours, change every 3000 hours</i>		

# CATERPILLAR WHEELED LOADERS 982M N8T (2014 AND AFTER)



USE		CLIMATE
Fluid analysis		Mediterranean
PRODUCT RECOMMENDATION 1		
<b>Gear Oil Alcat 30</b>		

*Check every 500 hours*

USE		CLIMATE
Fluid analysis		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agrisynth LSP Ultra 10W-40</b>	<b>Agrisynth MSP 10W-40</b>	<b>Agrifluid HT-Plus</b>

*Check every 500 hours*

USE		CLIMATE
Fluid analysis		Arctic
PRODUCT RECOMMENDATION 1		
<b>Agridiesel MSP 15W-40</b>		

*Check every 500 hours*

## CENTRAL LUBRICATION SYSTEM

Capacity: 4 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>MoS2 Grease EP 2</b>		

## COOLING SYSTEM

Capacity: 53 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Coolant SP 17</b>		

*Check every 10 hours, change every 72 months/ 12000 hours*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.