

# CATERPILLAR TRACKED LOADERS 939C

## HYSTAT (1997 AND AFTER)



**ENGINE 3046**  
Capacity: 13 liter

| USE                           |                             | CLIMATE                  |
|-------------------------------|-----------------------------|--------------------------|
| Normal                        |                             | Moderate                 |
| PRODUCT RECOMMENDATION 1      | PRODUCT RECOMMENDATION 2    | PRODUCT RECOMMENDATION 3 |
| <b>Agridiesel CRD+ 15W-40</b> | <b>Kroontrak MTH 10W-30</b> | <b>Asyntho 5W-30</b>     |

*Check every 10 hours, change every 100 hours*

**FINAL DRIVES**  
Capacity: 14,7 liter

| USE                      |  | CLIMATE       |
|--------------------------|--|---------------|
| Normal                   |  | Mediterranean |
| PRODUCT RECOMMENDATION 1 |  |               |
| <b>Gear Oil Alcat 50</b> |  |               |

*Check every 1 months/ 250 hours, change every 6 months/ 1000 hours*

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>Gear Oil Alcat 30</b> |  |          |

*Check every 1 months/ 250 hours, change every 6 months/ 1000 hours*

| USE                       |  | CLIMATE |
|---------------------------|--|---------|
| Normal                    |  | Arctic  |
| PRODUCT RECOMMENDATION 1  |  |         |
| <b>Gear Oil Alcat 10W</b> |  |         |

*Check every 1 months/ 250 hours, change every 6 months/ 1000 hours*

**HYDRAULIC SYSTEM**  
Capacity: 56,8 liter (Hydraulic tank)

| USE                           |                               | CLIMATE                   |
|-------------------------------|-------------------------------|---------------------------|
| Normal                        |                               | Moderate                  |
| PRODUCT RECOMMENDATION 1      | PRODUCT RECOMMENDATION 2      | PRODUCT RECOMMENDATION 3  |
| <b>Dieselfleet CD+ 15W-40</b> | <b>Multifleet SHPD 15W-40</b> | <b>Gear Oil Alcat 10W</b> |

*Check every 10 hours, change every 6 months/ 1000 hours*

| USE                       |  | CLIMATE  |
|---------------------------|--|----------|
| Biodegradable oil         |  | Moderate |
| PRODUCT RECOMMENDATION 1  |  |          |
| <b>Perlus Biosynth 46</b> |  |          |

*Check every 10 hours, change every 6 months/ 1000 hours*

# CATERPILLAR TRACKED LOADERS 939C HYSTAT (1997 AND AFTER)



## COOLING SYSTEM

Capacity: 21 liter

| USE                      |                          | CLIMATE                       |
|--------------------------|--------------------------|-------------------------------|
| Normal                   |                          | Moderate                      |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3      |
| <b>Coolant SP 15+</b>    | <b>Coolant SP 12</b>     | <b>Coolant -38 Organic NF</b> |

*Check every 10 hours, change every 24 months/ 3000 hours*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*