

CATERPILLAR MULTI TERRAIN LOADERS

297D XHP SERIES 2 HP2 (2015 AND AFTER)



ENGINE C3.8 Tier 4i
Capacity: 13,2 liter, Filter capacity: 1 liter

USE	CLIMATE
Preferred	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Agrisynth MSP 10W-40	Dieselfleet MSP 15W-40

Change every 500 hours/ 12 months

USE	CLIMATE
Preferred	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel MSP 15W-40	Dieselfleet LSP Ultra 10W-30	Dieselfleet MSP 10W-30

Change every 500 hours/ 12 months

USE	CLIMATE
Fluid analysis, preferred	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Agrisynth MSP 10W-40	Dieselfleet MSP 15W-40

Check every 250 hours

USE	CLIMATE
Fluid analysis, preferred	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel MSP 15W-40	Dieselfleet LSP Ultra 10W-30	Dieselfleet MSP 10W-30

Check every 250 hours

USE	CLIMATE
Alternative (acceptable)	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Agridiesel MSP 15W-40	Dieselfleet MSP 15W-40

Change every 500 hours/ 12 months

USE	CLIMATE
Alternative (acceptable)	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Dieselfleet LSP Ultra 10W-30	Dieselfleet MSP 10W-30

Change every 500 hours/ 12 months

USE	CLIMATE
Fluid analysis, alternative	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Agridiesel MSP 15W-40	Dieselfleet MSP 15W-40

Check every 250 hours

CATERPILLAR MULTI TERRAIN LOADERS

297D XHP SERIES 2 HP2 (2015 AND AFTER)



USE		CLIMATE
Fluid analysis, alternative		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Dieselfleet LSP Ultra 10W-30	Dieselfleet MSP 10W-30	
<i>Check every 250 hours</i>		

FINAL DRIVES		
Capacity: 1 liter (each)		
USE		CLIMATE
Preferred		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube Racing 75W-140		
<i>Check every 250 hours, change every 500 hours</i>		

USE		CLIMATE
Initial service (preferred)		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube Racing 75W-140		
<i>Change every 250 hours/ 6 months</i>		

USE		CLIMATE
Alternative (acceptable)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube Racing 75W-140	Gearlube HS GL-5 80W-140	
<i>Check every 250 hours, change every 500 hours</i>		

USE		CLIMATE
Initial service (alternative)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube Racing 75W-140	Gearlube HS GL-5 80W-140	
<i>Change every 250 hours/ 6 months</i>		

HYDRAULIC SYSTEM		
Capacity: 55 liter (Hydraulic system including tank), Capacity: 39 liter (Hydraulic tank)		
USE		CLIMATE
Preferred		Moderate
PRODUCT RECOMMENDATION 1		
Perlus Biosynth 46		
<i>Change every 36 months/ 3000 hours</i>		

CATERPILLAR MULTI TERRAIN LOADERS

297D XHP SERIES 2 HP2 (2015 AND AFTER)



USE		CLIMATE
Fluid analysis, preferred		Moderate
PRODUCT RECOMMENDATION 1		
Perlus Biosynth 46		

Check every 500 hours

USE		CLIMATE
Alternative (acceptable)		Mediterranean
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		

Change every 2000 hours/ 24 months

USE		CLIMATE
Alternative (acceptable)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP Ultra FE 5W-30	Agridiesel MSP 15W-40	Agridiesel CRD+ 15W-40

Change every 2000 hours/ 24 months

USE		CLIMATE
Fluid analysis, alternative		Mediterranean
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		

Check every 500 hours

USE		CLIMATE
Fluid analysis, alternative		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP Ultra FE 5W-30	Agridiesel MSP 15W-40	Agridiesel CRD+ 15W-40

Check every 500 hours

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		

CATERPILLAR MULTI TERRAIN LOADERS

297D XHP SERIES 2 HP2 (2015 AND AFTER)



COOLING SYSTEM

Capacity: 15,5 liter

USE		CLIMATE
Fluid analysis, preferred		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 17		

Check every 12 months, change every 72 months/ 12000 hours

USE		CLIMATE
Fluid analysis, initial (preferred)		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 17		

Check every 500 hours

USE		CLIMATE
Fluid analysis, alternative		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Check every 250 hours

AIRCONDITIONING COMPRESSOR

Capacity: 150 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

AIRCONDITIONING SYSTEM

Capacity: 810 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

TRACK ROLLER & IDLER AXLE TUBE

Capacity: 25-35 grams (each)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		

TRACK ROLLER & IDLER EXTERNAL BEARING

Capacity: 25-35 grams (each)

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.