CATERPILLAR VIBRATORY COMPACTORS CB/CC/CD/CP/CS CB-334D 3JZ



| ENGINE Caterpillar 3013C Capacity: 5,7 liter | | | | |
|--|--------------------------|--------------------------|--|--|
| USE | | CLIMATE | | |
| Normal | | Mediterranean | | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 | | |
| Agridiesel CRD+ 15W-40 | Dieselfleet CD+ 15W-40 | Multifleet SHPD 15W-40 | | |
| Check every 10 hours, change every | 250 hours/ 3 months | | | |
| USE | | CLIMATE | | |
| Normal | | Moderate | | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | | | |
| Synfleet SHPD 10W-40 | Multifleet SHPD 10W-40 | | | |
| Check every 10 hours, change every | 250 hours/ 3 months | | | |

| HYDRAULIC SYSTEM Capacity: 38 liter (Hydraulic tank) | | |
|--|---------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Multifleet SCD 30 | Gear Oil Alcat 30 | |
| Check every 10 hours, change eve | ery 1000 hours/ 12 months | |
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |

| Noma | | Moderate | |
|--|--------------------------|--------------------------|--|
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 | |
| Agridiesel CRD+ 15W-40 | Agrifluid HT-Plus | Kroontrak MTH 10W-30 | |
| Check every 10 hours, change every 1000 hours/ 12 months | | | |
| USE | | CLIMATE | |

| USE | CLIMATE |
|--------------------------|----------|
| Biodegradable oil | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Perlus Biosynth 46 | |
| | |

Check every 10 hours, change every 1000 hours/ 12 months

| GREASE POINTS/NIPPLES | |
|--------------------------|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| MoS2 Grease EP 2 | |

CATERPILLAR VIBRATORY COMPACTORS CB/CC/CD/CP/CS CB-334D 3JZ



| COOLING SYSTEM Capacity: 6,7 liter | | | |
|------------------------------------|--------------------------|----------|--|
| USE | | CLIMATE | |
| Normal | | Moderate | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | | |
| Coolant SP 15+ | Coolant SP 12 | | |
| Check every 10 hours, change ever | y 24 months/ 3000 hours | | |

VIBRATORY UNIT
Capacity: 2,2 liter

USE CLIMATE
Normal Moderate

PRODUCT RECOMMENDATION 1

Abacot MEP HD 220

Change every 3000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.