

CATERPILLAR VIBRATORY COMPACTORS

CB/CC/CD/CP/CS CB-424 6LD, DEUTZ



ENGINE Deutz
Capacity: 9,5 liter

USE
Normal

CLIMATE
Mediterranean

PRODUCT RECOMMENDATION 1

Multifleet SCD 40

PRODUCT RECOMMENDATION 2

Multifleet SCD 30

Check every 10 hours, change every 1 months/ 250 hours

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Kroontrak MTH 10W-30

PRODUCT RECOMMENDATION 2

Synfleet SHPD 10W-40

PRODUCT RECOMMENDATION 3

Dieselfleet CD+ 15W-40

Check every 10 hours, change every 1 months/ 250 hours

USE
Normal

CLIMATE
Cold

PRODUCT RECOMMENDATION 1

Multifleet SCD 10W

Check every 10 hours, change every 1 months/ 250 hours

TRANSFERBOX

Capacity: 0,75 liter

USE
Normal

CLIMATE
Mediterranean

PRODUCT RECOMMENDATION 1

Gearlube GL-5 85W-140

PRODUCT RECOMMENDATION 2

Unigear LS GL-3/GL-5 85W-140

Check every 10 hours, change every 3 months/ 500 hours

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1011

PRODUCT RECOMMENDATION 2

Syngear TDL 75W-90

PRODUCT RECOMMENDATION 3

Gearlube GL-5 80W-90

Check every 10 hours, change every 3 months/ 500 hours

USE
Normal

CLIMATE
Arctic

PRODUCT RECOMMENDATION 1

SP Gear 5015

PRODUCT RECOMMENDATION 2

SP Gear 1071

Check every 10 hours, change every 3 months/ 500 hours

CATERPILLAR VIBRATORY COMPACTORS

CB/CC/CD/CP/CS CB-424 6LD, DEUTZ



HYDRAULIC SYSTEM

Capacity: 42 liter (Hydraulic tank)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gear Oil Alcat 10W

Check every 10 hours, change every 2000 hours/ 12 months

GREASE POINTS/NIPPLES

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

MoS2 Grease EP 2

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.