

CATERPILLAR VIBRATORY COMPACTORS

CB/CC/CD/CP/CS CB44B JXL/NSL/TWC

(2012 AND AFTER)



ENGINE C3.4B
Capacity: 9 liter

USE	CLIMATE
Preferred	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Agrisynth MSP 10W-40	Dieselfleet MSP 15W-40

Check every 10 hours, change every 500 hours/ 6 months

USE	CLIMATE
Preferred	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP Ultra 10W-40	Agridiesel MSP 15W-40	Armado Synth LSP Ultra 10W-40

Check every 10 hours, change every 500 hours/ 6 months

USE	CLIMATE
Fluid analysis, preferred	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Agrisynth MSP 10W-40	Dieselfleet MSP 15W-40

Check every 3 months/ 250 hours

USE	CLIMATE
Fluid analysis, preferred	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP Ultra 10W-40	Agridiesel MSP 15W-40	Armado Synth LSP Ultra 10W-40

Check every 3 months/ 250 hours

USE	CLIMATE
Alternative (acceptable)	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Agridiesel MSP 15W-40	Dieselfleet MSP 15W-40

Check every 10 hours, change every 500 hours/ 6 months

USE	CLIMATE
Alternative (acceptable)	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Armado Synth MSP 5W-40	Dieselfleet LSP Ultra 10W-30	Dieselfleet MSP 10W-30

Check every 10 hours, change every 500 hours/ 6 months

USE	CLIMATE
Fluid analysis, alternative	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Agridiesel MSP 15W-40	Dieselfleet MSP 15W-40

Check every 3 months/ 250 hours

CATERPILLAR VIBRATORY COMPACTORS

CB/CC/CD/CP/CS CB44B JXL/NSL/TWC

(2012 AND AFTER)



USE		CLIMATE
Fluid analysis, alternative		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Armado Synth MSP 5W-40	Dieselfleet LSP Ultra 10W-30	Dieselfleet MSP 10W-30
<i>Check every 3 months/ 250 hours</i>		

HYDRAULIC SYSTEM		
Capacity: 32,6 liter		
USE		CLIMATE
Preferred, extended		Moderate
PRODUCT RECOMMENDATION 1		
Perlus Biosynth 46		
<i>Check every 10 hours, change every 18 months/ 3000 hours</i>		

USE		CLIMATE
Fluid analysis, preferred		Moderate
PRODUCT RECOMMENDATION 1		
Perlus Biosynth 46		
<i>Check every 6 months/ 500 hours</i>		

USE		CLIMATE
Alternative (acceptable)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth MSP 10W-40	Agridiesel MSP 15W-40	Agridiesel CRD+ 15W-40
<i>Check every 10 hours, change every 2000 hours/ 12 months</i>		

USE		CLIMATE
Fluid analysis, alternative		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth MSP 10W-40	Agridiesel MSP 15W-40	Agridiesel CRD+ 15W-40
<i>Check every 6 months/ 500 hours</i>		

EXTERNAL GREASE POINTS		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		
<i>Check every 50 hours</i>		

CATERPILLAR VIBRATORY COMPACTORS

CB/CC/CD/CP/CS CB44B JXL/NSL/TWC

(2012 AND AFTER)



GREASE POINTS/NIPPLES DRIVE SHAFT

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
HT Q9 High Grade Grease		
<i>Check every 50 hours</i>		

GREASE POINTS/NIPPLES STEERING COLUMN

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
HT Q9 High Grade Grease		
<i>Check every 3 months/ 250 hours</i>		

COOLING SYSTEM

Capacity: 16-18 liter

USE		CLIMATE
Fluid analysis, preferred		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 17		
<i>Check every 12 months, change every 72 months/ 12000 hours</i>		

USE		CLIMATE
Fluid analysis, initial (preferred)		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 17		
<i>Check every 500 hours</i>		

USE		CLIMATE
Fluid analysis, alternative		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF
<i>Check every 3 months/ 500 hours</i>		

ECCENTRIC WEIGHT HOUSING SOLID DRUM

Capacity: 12 liter (each)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Abacot MEP HD 220		
<i>Check every 100 hours, change every 24 months/ 3000 hours</i>		

CATERPILLAR VIBRATORY COMPACTORS

CB/CC/CD/CP/CS CB44B JXL/NSL/TWC

(2012 AND AFTER)



ECCENTRIC WEIGHT HOUSING SPLIT DRUM

Capacity: 7,3 liter (each)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Abacot MEP HD 220*Check every 100 hours, change every 1000 hours/ 12 months*

FINAL DRIVE SOLID DRUM

Capacity: 0,9 liter (each)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube Racing 75W-140

PRODUCT RECOMMENDATION 2

Gearlube HS GL-5 80W-140*Check every 100 hours, change every 500 hours*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

Gearlube Racing 75W-140

PRODUCT RECOMMENDATION 2

Gearlube HS GL-5 80W-140*Change every 250 hours*

FINAL DRIVE SPLIT DRUM

Capacity: 3,9 liter (each)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Abacot MEP HD 220*Check every 100 hours, change every 1000 hours/ 12 months*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

Abacot MEP HD 220*Change every 50 hours*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.