

CATERPILLAR FORKLIFT TRUCKS, GAS/LPG/PETROL GC15 MITSUBISHI 4G63 (1992-1999)

**ENGINE (LPG) Mitsubishi 4G63**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Kroontrak MTH 10W-30	Multifleet SHPD 15W-40	

Change every 1 months/ 200 hours

DIFFERENTIAL AND FINAL DRIVES FRONT

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-4 80W-90	Unigear HS GL-3/GL-5 80W-90	

USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid HT-Plus	SP Gear 5015	Gearlube GL-4 80W

TORQUE CONVERTER

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		

Change every 6 months/ 1200 hours

TRANSMISSION Powershift

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
ATF-A		

CATERPILLAR FORKLIFT TRUCKS, GAS/LPG/PETROL GC15 MITSUBISHI 4G63 (1992-1999)



HYDRAULIC SYSTEM

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Perlus H 32*Change every 12 months/ 2400 hours*

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1

Perlus H 22*Change every 12 months/ 2400 hours*

HYDRAULIC BRAKE SYSTEM

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4

PRODUCT RECOMMENDATION 2

Drauliquid-S DOT 4

PRODUCT RECOMMENDATION 3

Drauliquid DOT 3*Change every 12 months/ 2400 hours*

GREASE POINTS/NIPPLES CHASSIS

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gear Grease EP 1

GREASE POINTS/NIPPLES WHEEL BEARINGS

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Labora Grease

PRODUCT RECOMMENDATION 2

Q5 MP Calcep Grease EP 2

PRODUCT RECOMMENDATION 3

MP Lithep Grease EP 2

CATERPILLAR FORKLIFT TRUCKS, GAS/LPG/PETROL GC15 MITSUBISHI 4G63 (1992-1999)

**DRIVE GEARS**

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-4 80W-90	Unigear HS GL-3/GL-5 80W-90	

Change every 6 months/ 1200 hours

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid HT-Plus	SP Gear 5015	Gearlube GL-4 80W

Change every 6 months/ 1200 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.