PRODUCT RECOMMENDATION

CATERPILLAR FORKLIFT TRUCKS, DIESEL DP120N MITSUBISHI 6M60-TL (2008 AND AFTER)

ENGINE Mitsubishi 6M60-TL
Capacity: 16 liter (Total), Filter capacity: 4 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1		
Multifleet SCD 30		

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1		
Multifleet SCD 20W-20		

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Kroontrak MTH 10W-30	**Multifleet SCD 10W**	

DIFFERENTIAL AND FINAL DRIVES FRONT
Capacity: 20 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube GL-4 80W-90	**Gearlube GL-5 80W-90**	**Unigear HS GL-3/GL-5 80W-90**

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid HT-Plus	**SP Gear 5015**	**SP Gear 1071**

TORQUE CONVERTER

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

CATERPILLAR FORKLIFT TRUCKS, DIESEL DP120N MITSUBISHI 6M60-TL (2008 AND AFTER)

HYDRAULIC SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Perlus H 32		

HYDRAULIC BRAKE SYSTEM
Capacity: 0,23 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Drauliquid-LV Super DOT 4	**Drauliquid-S DOT 4**	**Drauliquid DOT 3**

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gear Grease EP 1		

GREASE POINTS/NIPPLES WHEEL BEARINGS

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	**Q5 MP Calcep Grease EP 2**	**MP Lithep Grease EP 2**

COOLING SYSTEM
Capacity: 18 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	**Coolant -26**	

Check every 10 hours, change every 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367