CATERPILLAR TRACKED EXCAVATORS 225 61X (1972-1987)



ENGINE Capacity: 12,3 liter			
USE		CLIMATE	
Normal		Mediterranean	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Multifleet SCD 40	Multifleet SCD 30		
Change every 250 hours/ 1 months			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Kroontrak MTH 10W-30	Synfleet SHPD 10W-40	Dieselfleet CD+ 15W-40	
Change every 250 hours/ 1 months			
USE		CLIMATE	
Normal		Cold	
PRODUCT RECOMMENDATION 1			
Multifleet SCD 10W			
Change every 250 hours/ 1 months			

FINAL DRIVES Capacity: 11,4 liter (each side)	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Multifleet SCD 50	

FINAL DRIVES HEAVY DUTY Capacity: 53 liter		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Multifleet SCD 50		

CATERPILLAR TRACKED EXCAVATORS 225 61X (1972-1987)



SWING DRIVE Capacity: 28 liter	
use Normal	сымате Moderate
PRODUCT RECOMMENDATION 1 Multifleet SCD 50	

Check every 1 months/ 250 hours

HYDRAULIC SYSTEM Capacity: 303 liter	
USE	CLIMATE
Normal	Mediterranean
PRODUCT RECOMMENDATION 1	
Gear Oil Alcat 30	
Check every 3 months/ 500 hours, change every 12 months/ 2000 hours	

use Normal	сымате Moderate
PRODUCT RECOMMENDATION 1 Gear Oil Alcat 10W	

Check every 3 months/ 500 hours, change every 12 months/ 2000 hours

COOLING SYSTEM Capacity: 38 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant SP 17	
Ohamma and 0000 have / 40 manually	

Change every 2000 hours/ 12 months

CLAMSHELL ROTATOR GEAR DRIVE Capacity: 1,4 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Multifleet SCD 30	
Check every 50 hours	

CATERPILLAR TRACKED EXCAVATORS 225 61X (1972-1987)



PUMP DRIVE Capacity: 5,7 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40	Multifleet SCD 30

Change every 2000 hours/ 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.