

CATERPILLAR TRACKED EXCAVATORS

235C 3WG (1989-1992)

**ENGINE**

Capacity: 27 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Agridiesel CRD+ 15W-40****PRODUCT RECOMMENDATION 2****Dieselfleet CD+ 15W-40****PRODUCT RECOMMENDATION 3****Multifleet SHPD 15W-40***Change every 250 hours/ 1 months***FINAL DRIVES**

Capacity: 53 liter (each side)

USE

Normal

CLIMATE

Mediterranean

PRODUCT RECOMMENDATION 1**Gear Oil Alcat 50****USE**

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Gear Oil Alcat 30****USE**

Normal

CLIMATE

Arctic

PRODUCT RECOMMENDATION 1**Gear Oil Alcat 10W****HYDRAULIC SYSTEM**

Capacity: 329 liter

USE

Normal

CLIMATE

Mediterranean

PRODUCT RECOMMENDATION 1**Gear Oil Alcat 30***Check every 3 months/ 500 hours, change every 12 months/ 2000 hours***USE**

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Agridiesel CRD+ 15W-40****PRODUCT RECOMMENDATION 2****Dieselfleet CD+ 15W-40****PRODUCT RECOMMENDATION 3****Multifleet SHPD 15W-40***Check every 3 months/ 500 hours, change every 12 months/ 2000 hours*

CATERPILLAR TRACKED EXCAVATORS

235C 3WG (1989-1992)



GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		

COOLING SYSTEM

Capacity: 46 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 17		

Change every 24 months/ 3000 hours

CLAMSHELL ROTATOR GEAR DRIVE

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Multifleet SCD 30		

PUMP DRIVE

Capacity: 6,6 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 50		

Check every 50 hours, change every 12 months/ 2000 hours

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		

Check every 50 hours, change every 12 months/ 2000 hours

USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		

Check every 50 hours, change every 12 months/ 2000 hours

CATERPILLAR TRACKED EXCAVATORS

235C 3WG (1989-1992)



SWING REDUCTION UNIT

Capacity: 34 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Gear Oil Alcat 50*Check every 1 months/ 250 hours*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gear Oil Alcat 30*Check every 1 months/ 250 hours*

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1

Gear Oil Alcat 10W*Check every 1 months/ 250 hours*

TRACK PINS

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Multifleet SCD 30

TRACK ROLLERS & IDLERS

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Gear Oil Alcat 50

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gear Oil Alcat 30

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1

Gear Oil Alcat 10W

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or

CATERPILLAR TRACKED EXCAVATORS

235C 3WG (1989-1992)



inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.