

CATERPILLAR TRACKED EXCAVATORS

329E L (2011 AND AFTER)

**ENGINE**

Capacity: 29,5 liter

| USE | | CLIMATE |
|------------------------------|-------------------------------|---------------|
| Preferred | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Agridiesel MSP 15W-40 | Dieselfleet MSP 15W-40 | |

Check every 10 hours, change every 3 months/ 500 hours

| USE | | CLIMATE |
|-------------------------------|-------------------------------------|-------------------------------|
| Preferred | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Armado Synth MSP 5W-40 | Dieselfleet LSP Ultra 10W-30 | Dieselfleet MSP 10W-30 |

Check every 10 hours, change every 3 months/ 500 hours

| USE | | CLIMATE |
|-----------------------------|-------------------------------|---------------|
| Alternative (acceptable) | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Agrisynth MSP 10W-40 | Dieselfleet MSP 15W-40 | |

Check every 10 hours, change every 3 months/ 500 hours

| USE | | CLIMATE |
|-----------------------------------|------------------------------|--------------------------------------|
| Alternative (acceptable) | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agrisynth LSP Ultra 10W-40 | Agridiesel MSP 15W-40 | Armado Synth LSP Ultra 10W-40 |

*Check every 10 hours, change every 3 months/ 500 hours***HYDRAULIC SYSTEM**

Capacity: 165 liter

| USE | | CLIMATE |
|--------------------------|--|---------------|
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | | |
| Gear Oil Alcat 30 | | |

Check every 10 hours, change every 2000 hours/ 12 months

| USE | | CLIMATE |
|-----------------------------|-------------------------------|----------------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Kroontrak CVT 10W-40 | Agridiesel CRD+ 15W-40 | Agrifluid Synth XHP Ultra |

Check every 10 hours, change every 2000 hours/ 12 months

CATERPILLAR TRACKED EXCAVATORS

329E L (2011 AND AFTER)



| USE | | CLIMATE |
|--------------------------|--|---------------|
| Continuous hammer use | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | | |
| Gear Oil Alcat 30 | | |

Check every 10 hours, change every 600 hours

| USE | | CLIMATE |
|-----------------------------|-------------------------------|----------------------------------|
| Continuous hammer use | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Kroontrak CVT 10W-40 | Agridiesel CRD+ 15W-40 | Agrifluid Synth XHP Ultra |

Check every 10 hours, change every 600 hours

| USE | | CLIMATE |
|--------------------------|--|---------------|
| Partial hammer use (50%) | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | | |
| Gear Oil Alcat 30 | | |

Check every 10 hours, change every 1000 hours

| USE | | CLIMATE |
|-----------------------------|-------------------------------|----------------------------------|
| Partial hammer use (50%) | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Kroontrak CVT 10W-40 | Agridiesel CRD+ 15W-40 | Agrifluid Synth XHP Ultra |

Check every 10 hours, change every 1000 hours

COOLING SYSTEM

Capacity: 30 liter

| USE | | CLIMATE |
|--------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Coolant SP 17 | | |

Check every 10 hours, change every 72 months/ 12000 hours

SWING GEAR

Capacity: 21,4 liter

| USE | | CLIMATE |
|--------------------------|---------------------------------|------------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 |

Change every 2000 hours/ 12 months

CATERPILLAR TRACKED EXCAVATORS

329E L (2011 AND AFTER)



SWING REDUCTION UNIT

Capacity: 10 liter

| USE | | CLIMATE |
|--------------------------|--------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gear Oil Alcat 30 | Gear Oil Alcat 50 | |

Check every 1 months/ 250 hours, change every 6 months/ 1000 hours

| USE | | CLIMATE |
|---------------------------|--|---------|
| Normal | | Arctic |
| PRODUCT RECOMMENDATION 1 | | |
| Gear Oil Alcat 10W | | |

Check every 1 months/ 250 hours, change every 6 months/ 1000 hours

| USE | | CLIMATE |
|--------------------------|--------------------------|----------|
| Initial service | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gear Oil Alcat 30 | Gear Oil Alcat 50 | |

Change every 250 hours

| USE | | CLIMATE |
|---------------------------|--|---------|
| Initial service | | Arctic |
| PRODUCT RECOMMENDATION 1 | | |
| Gear Oil Alcat 10W | | |

Change every 250 hours

CATERPILLAR TRACKED EXCAVATORS

329E L (2011 AND AFTER)


TRAVEL REDUCTION UNIT

Capacity: 6 liter

| USE | | CLIMATE |
|--------------------------|--------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gear Oil Alcat 30 | Gear Oil Alcat 50 | |

Check every 1 months/ 250 hours, change every 12 months/ 2000 hours

| USE | | CLIMATE |
|---------------------------|--|---------|
| Normal | | Arctic |
| PRODUCT RECOMMENDATION 1 | | |
| Gear Oil Alcat 10W | | |

Check every 1 months/ 250 hours, change every 12 months/ 2000 hours

| USE | | CLIMATE |
|--------------------------|--------------------------|----------|
| Initial service | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gear Oil Alcat 30 | Gear Oil Alcat 50 | |

Change every 250 hours

| USE | | CLIMATE |
|---------------------------|--|---------|
| Initial service | | Arctic |
| PRODUCT RECOMMENDATION 1 | | |
| Gear Oil Alcat 10W | | |

Change every 250 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.