

# CATERPILLAR WHEELED EXCAVATORS

## 212 (1993 AND AFTER)



**ENGINE** Deutz  
Capacity: 13 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Multifleet SCD 40</b>	<b>Multifleet SCD 30</b>	

*Change every 500 hours/ 3 months*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agridiesel CRD+ 15W-40</b>	<b>Kroontrak MTH 10W-30</b>	<b>Synfleet SHPD 10W-40</b>

*Change every 500 hours/ 3 months*

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1		
<b>Multifleet SCD 10W</b>		

*Change every 500 hours/ 3 months*

**ENGINE** Perkins  
Capacity: 9,4 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Multifleet SCD 40</b>	<b>Multifleet SCD 30</b>	

*Change every 250 hours/ 1 months*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agridiesel CRD+ 15W-40</b>	<b>Kroontrak MTH 10W-30</b>	<b>Synfleet SHPD 10W-40</b>

*Change every 250 hours/ 1 months*

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1		
<b>Multifleet SCD 10W</b>		

*Change every 250 hours/ 1 months*

# CATERPILLAR WHEELED EXCAVATORS

## 212 (1993 AND AFTER)



### DIFFERENTIAL STEERED AXLE

Capacity: 9,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Gearlube LS 80W-90***Change every 2000 hours/ 12 months*

### HUB REDUCTIONS

Capacity: 2,5 liter (each hub)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Gearlube LS 80W-90***Change every 2000 hours/ 12 months*

### TRANSAXLE

Capacity: 15 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Gearlube LS 80W-90***Change every 2000 hours/ 12 months*

### HYDRAULIC SYSTEM

Capacity: 270 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

**Gear Oil Alcat 30***Change every 2000 hours/ 12 months*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Gear Oil Alcat 10W***Change every 2000 hours/ 12 months*

# CATERPILLAR WHEELED EXCAVATORS

## 212 (1993 AND AFTER)



### GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>MoS2 Grease EP 2</b>		

### COOLING SYSTEM

Capacity: 30 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Coolant SP 17</b>		

*Change every 2000 hours/ 12 months*

### SWING DRIVE UNIT

Capacity: 9,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>SP Gear 1011</b>	<b>Syngear TDL 75W-90</b>	<b>Gearlube GL-5 80W-90</b>

*Change every 2000 hours/ 12 months*

USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>SP Gear 5015</b>	<b>SP Gear 1071</b>	

*Change every 2000 hours/ 12 months*

### TRAVEL BRAKE SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Multifleet SCD 10W</b>		

*Change every 2000 hours/ 12 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.