

CATERPILLAR WHEELED EXCAVATORS

M315C H2B (2005 AND AFTER)



ENGINE 3054E ATAAC
Capacity: 8 liter

| USE | CLIMATE |
|----------------------|---------------|
| Extended drain (max) | Mediterranean |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|------------------------------|-------------------------------|-------------------------------|
| Agridiesel MSP 15W-40 | Agridiesel CRD+ 15W-40 | Multifleet SHPD 15W-40 |

Change every 250 hours/ 1 months

| USE | CLIMATE |
|----------------------|----------|
| Extended drain (max) | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|-----------------------------|-----------------------------|----------------------------|
| Agrisynth LSP 10W-40 | Agrisynth MSP 10W-40 | Armado Synth 10W-40 |

Change every 250 hours/ 1 months

| USE | CLIMATE |
|--------|---------------|
| Normal | Mediterranean |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|------------------------------|-------------------------------|-------------------------------|
| Agridiesel MSP 15W-40 | Agridiesel CRD+ 15W-40 | Multifleet SHPD 15W-40 |

Change every 500 hours/ 3 months

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|-----------------------------|-----------------------------|----------------------------|
| Agrisynth LSP 10W-40 | Agrisynth MSP 10W-40 | Armado Synth 10W-40 |

Change every 500 hours/ 3 months

DIFFERENTIAL FRONT
Capacity: 10,5-11,6 liter

| USE | CLIMATE |
|--|----------|
| Travelling time > 25% of operating hours | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|--------------------------|-----------------------------|--------------------------|
| Agrifluid HT-Plus | Kroontrak MTH 10W-30 | Agrifluid HT |

Change every 1500 hours/ 12 months

| USE | CLIMATE |
|--|----------|
| Travelling time < 25% of operating hours | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|--------------------------|-----------------------------|--------------------------|
| Agrifluid HT-Plus | Kroontrak MTH 10W-30 | Agrifluid HT |

Change every 2000 hours/ 12 months

CATERPILLAR WHEELED EXCAVATORS

M315C H2B (2005 AND AFTER)



DIFFERENTIAL REAR

Capacity: 14-15,5 liter

| USE | | CLIMATE |
|--|-----------------------------|--------------------------|
| Travelling time > 25% of operating hours | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agrifluid HT-Plus | Kroontrak MTH 10W-30 | Agrifluid HT |

Change every 1500 hours/ 12 months

| USE | | CLIMATE |
|--|-----------------------------|--------------------------|
| Travelling time < 25% of operating hours | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agrifluid HT-Plus | Kroontrak MTH 10W-30 | Agrifluid HT |

Change every 2000 hours/ 12 months

FINAL DRIVES

Capacity: 2,5 liter

| USE | | CLIMATE |
|--|-----------------------------|--------------------------|
| Travelling time > 25% of operating hours | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agrifluid HT-Plus | Kroontrak MTH 10W-30 | Agrifluid HT |

Change every 1500 hours/ 12 months

| USE | | CLIMATE |
|--|-----------------------------|--------------------------|
| Travelling time < 25% of operating hours | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agrifluid HT-Plus | Kroontrak MTH 10W-30 | Agrifluid HT |

Change every 2000 hours/ 12 months

CATERPILLAR WHEELED EXCAVATORS

M315C H2B (2005 AND AFTER)



TRANSMISSION

Capacity: 2,5 liter

| USE | CLIMATE |
|--|---------------|
| Travelling time > 25% of operating hours | Mediterranean |

| PRODUCT RECOMMENDATION 1 | | |
|--------------------------|--|--|
| Gear Oil Alcat 30 | | |

Change every 1500 hours/ 12 months

| USE | CLIMATE |
|--|----------|
| Travelling time > 25% of operating hours | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|-------------------------------|-----------------------------|-------------------------------|
| Agridiesel CRD+ 15W-40 | Synfleet SHPD 10W-40 | Dieselfleet CD+ 15W-40 |

Change every 1500 hours/ 12 months

| USE | CLIMATE |
|--|---------------|
| Travelling time < 25% of operating hours | Mediterranean |

| PRODUCT RECOMMENDATION 1 | | |
|--------------------------|--|--|
| Gear Oil Alcat 30 | | |

Change every 2000 hours/ 12 months

| USE | CLIMATE |
|--|----------|
| Travelling time < 25% of operating hours | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|-------------------------------|-----------------------------|-------------------------------|
| Agridiesel CRD+ 15W-40 | Synfleet SHPD 10W-40 | Dieselfleet CD+ 15W-40 |

Change every 2000 hours/ 12 months

HYDRAULIC SYSTEM

Capacity: 135 liter (Hydraulic tank), Capacity: 255 liter (Total)

| USE | CLIMATE |
|--------|---------------|
| Normal | Mediterranean |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|--------------------------|--------------------------|--|
| Multifleet SCD 30 | Gear Oil Alcat 30 | |

Change every 2000 hours/ 12 months

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|-------------------------------|--------------------------|-----------------------------|
| Agridiesel CRD+ 15W-40 | Agrifluid HT-Plus | Kroontrak MTH 10W-30 |

Change every 2000 hours/ 12 months

CATERPILLAR WHEELED EXCAVATORS

M315C H2B (2005 AND AFTER)



| USE | | CLIMATE |
|--------------------------|--------------------------|---------------|
| 50% use of breaker | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Multifleet SCD 30 | Gear Oil Alcat 30 | |

Change every 1000 hours

| USE | | CLIMATE |
|-------------------------------|--------------------------|-----------------------------|
| 50% use of breaker | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agridiesel CRD+ 15W-40 | Agrifluid HT-Plus | Kroontrak MTH 10W-30 |

Change every 1000 hours

| USE | | CLIMATE |
|--------------------------|--------------------------|---------------|
| 100% use of breaker | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Multifleet SCD 30 | Gear Oil Alcat 30 | |

Change every 600 hours

| USE | | CLIMATE |
|-------------------------------|--------------------------|-----------------------------|
| 100% use of breaker | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agridiesel CRD+ 15W-40 | Agrifluid HT-Plus | Kroontrak MTH 10W-30 |

Change every 600 hours

GREASE POINTS/NIPPLES

| USE | | CLIMATE |
|--------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| MoS2 Grease EP 2 | | |

| USE | | CLIMATE |
|--------------------------------|--|----------|
| Light Duty | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| HT Q9 High Grade Grease | | |

CATERPILLAR WHEELED EXCAVATORS

M315C H2B (2005 AND AFTER)



COOLING SYSTEM

Capacity: 32 liter

| USE | CLIMATE |
|----------------------|----------|
| Extended drain (max) | Moderate |

| | | |
|--------------------------|--|--|
| PRODUCT RECOMMENDATION 1 | | |
| Coolant SP 17 | | |

Check every 500 hours, change every 36 months/ 6000 hours

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| | | |
|--------------------------|--|--|
| PRODUCT RECOMMENDATION 1 | | |
| Coolant SP 17 | | |

Check every 500 hours, change every 12 months/ 2000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.