PRODUCT RECOMMENDATION

CATERPILLAR FOREST SWING MACHINES 324D FM TIER 3 JGK (2006-2011)

ENGINE C7 Acert
Capacity: 34 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
Agridiesel CRD+ 15W-40	**Multifleet SHPD 15W-40**	

Check every 10 hours, change every 3 months/ 500 hours

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Agrisynth LSP 10W-40	**Synfleet SHPD 10W-40**	**Dieselfleet CD+ 15W-40**

Check every 10 hours, change every 3 months/ 500 hours

USE		CLIMATE
Fluid analysis		Mediterranean
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
Agridiesel CRD+ 15W-40	**Multifleet SHPD 15W-40**	

Check every 250 hours

USE		CLIMATE
Fluid analysis		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Agrisynth LSP 10W-40	**Synfleet SHPD 10W-40**	**Dieselfleet CD+ 15W-40**

Check every 250 hours

HYDRAULIC CAB TILT SYSTEM
Capacity: 7,2 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Agridiesel CRD+ 15W-40	**Dieselfleet CD+ 15W-40**	**Multifleet SHPD 15W-40**

Check every 10 hours, change every 2000 hours/ 12 months

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Kroontrak CVT 10W-40	**Kroontrak MTH 10W-30**	**Synfleet SHPD 10W-40**

Check every 10 hours, change every 2000 hours/ 12 months

HYDRAULIC SYSTEM
Capacity: 245 liter (Change capacity)

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

CATERPILLAR FOREST SWING MACHINES 324D FM TIER 3 JGK (2006-2011)

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	**Dieselfleet CD+ 15W-40**	**Multifleet SHPD 15W-40**
Check every 10 hours, change every 2000 hours/ 12 months		

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak CVT 10W-40	**Kroontrak MTH 10W-30**	**Synfleet SHPD 10W-40**
Check every 10 hours, change every 2000 hours/ 12 months		

USE		CLIMATE
Biodegradable oil		Moderate
PRODUCT RECOMMENDATION 1		
Perlus Biosynth 46		
Check every 10 hours, change every 2000 hours/ 12 months		

USE		CLIMATE
Fluid analysis		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	**Dieselfleet CD+ 15W-40**	**Multifleet SHPD 15W-40**
Check every 500 hours		

USE		CLIMATE
Fluid analysis		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak CVT 10W-40	**Kroontrak MTH 10W-30**	**Synfleet SHPD 10W-40**
Check every 500 hours		

USE		CLIMATE
Biodegradable oil, fluid analysis		Moderate
PRODUCT RECOMMENDATION 1		
Perlus Biosynth 46		
Check every 500 hours		

CENTRAL LUBRICATION SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

CATERPILLAR FOREST SWING MACHINES 324D FM TIER 3 JGK (2006-2011)

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
HT Q9 High Grade Grease	**Labora Grease**	

COOLING SYSTEM
Capacity: 30 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 17		

Check every 10 hours, change every 72 months/ 12000 hours

USE		CLIMATE
Fluid analysis		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 17		

Check every 250 hours

HUB VARIABLE FAN
Capacity: 1,3 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 50		

Check every 6 months/ 1000 hours, change every 48 months/ 6000 hours

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		

Check every 6 months/ 1000 hours, change every 48 months/ 6000 hours

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

CATERPILLAR FOREST SWING MACHINES 324D FM TIER 3 JGK (2006-2011)

PIVOT SHAFT BEARINGS

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 50		

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		

USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		

SWING GEAR
Capacity: 21,4 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	**Q5 MP Calcep Grease EP 2**	**MP Lithep Grease EP 2**

Change every 2000 hours/ 12 months

SWING REDUCTION UNIT
Capacity: 8 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gear Oil Alcat 30	**Gear Oil Alcat 50**	

Check every 1 months/ 250 hours, change every 1000 hours/ 12 months

USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		

Check every 1 months/ 250 hours, change every 1000 hours/ 12 months

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

CATERPILLAR FOREST SWING MACHINES 324D FM TIER 3 JGK (2006-2011)

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gear Oil Alcat 30	**Gear Oil Alcat 50**	
Change every 250 hours/ 6 months		

USE		CLIMATE
Initial service		Arctic
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		
Change every 250 hours/ 6 months		

USE		CLIMATE
Fluid analysis		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gear Oil Alcat 30	**Gear Oil Alcat 50**	
Check every 500 hours		

USE		CLIMATE
Fluid analysis		Arctic
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		
Check every 500 hours		

TRACK IDLERS

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Multifleet SCD 40		

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Multifleet SCD 30		

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

CATERPILLAR FOREST SWING MACHINES 324D FM TIER 3 JGK (2006-2011)

TRACK ROLLER FRAME RECOIL SPRING

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 50		

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		

USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		

TRACK ROLLERS

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Multifleet SCD 40		

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Multifleet SCD 30		

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

CATERPILLAR FOREST SWING MACHINES 324D FM TIER 3 JGK (2006-2011)

TRAVEL REDUCTION UNIT
Capacity: 8 liter (each)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
Gear Oil Alcat 30	**Gear Oil Alcat 50**	
Check every 1 months/ 250 hours, change every 12 months/ 2000 hours		

USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		
Check every 1 months/ 250 hours, change every 12 months/ 2000 hours		

USE		CLIMATE
Fluid analysis		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
Gear Oil Alcat 30	**Gear Oil Alcat 50**	
Check every 250 hours		

USE		CLIMATE
Fluid analysis		Arctic
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		
Check every 250 hours		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367