

# CATERPILLAR MOTOR GRADERS 120M B9N (2005 AND AFTER)



**ENGINE** C6.6 Acert  
Capacity: 14,3 liter

| USE    | CLIMATE       |
|--------|---------------|
| Normal | Mediterranean |

| PRODUCT RECOMMENDATION 1     | PRODUCT RECOMMENDATION 2      |  |
|------------------------------|-------------------------------|--|
| <b>Agridiesel MSP 15W-40</b> | <b>Dieselfleet MSP 15W-40</b> |  |

*Check every 10 hours, change every 3 months/ 500 hours*

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1      | PRODUCT RECOMMENDATION 2            | PRODUCT RECOMMENDATION 3      |
|-------------------------------|-------------------------------------|-------------------------------|
| <b>Armado Synth MSP 5W-40</b> | <b>Dieselfleet LSP Ultra 10W-30</b> | <b>Dieselfleet MSP 10W-30</b> |

*Check every 10 hours, change every 3 months/ 500 hours*

| USE             | CLIMATE       |
|-----------------|---------------|
| Initial service | Mediterranean |

| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2      |  |
|-----------------------------|-------------------------------|--|
| <b>Agrisynth MSP 10W-40</b> | <b>Dieselfleet MSP 15W-40</b> |  |

*Check every 10 hours, change every 3 months/ 500 hours*

| USE             | CLIMATE  |
|-----------------|----------|
| Initial service | Moderate |

| PRODUCT RECOMMENDATION 1          | PRODUCT RECOMMENDATION 2     | PRODUCT RECOMMENDATION 3             |
|-----------------------------------|------------------------------|--------------------------------------|
| <b>Agrisynth LSP Ultra 10W-40</b> | <b>Agridiesel MSP 15W-40</b> | <b>Armado Synth LSP Ultra 10W-40</b> |

*Check every 10 hours, change every 3 months/ 500 hours*

**GEARBOX ALL WHEEL DRIVE**  
Capacity: 7 liter (each side)

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 |  |  |
|--------------------------|--|--|
| <b>Gear Oil Alcat 50</b> |  |  |

*Check every 3 months/ 500 hours, change every 24 months/ 2000 hours*

**TANDEM DRIVE**  
Capacity: 59,2 liter (each side)

We are unable to give a standard recommendation for this component. Please contact our service department.

# CATERPILLAR MOTOR GRADERS 120M B9N

## (2005 AND AFTER)

**TRANSAXLE**

Capacity: 62,5 liter

| USE                      |                          | CLIMATE       |
|--------------------------|--------------------------|---------------|
| Normal                   |                          | Mediterranean |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |               |
| <b>Gear Oil Alcat 30</b> | <b>Gear Oil Alcat 50</b> |               |

*Check every 10 hours, change every 6 months/ 1000 hours*

| USE                       |  | CLIMATE |
|---------------------------|--|---------|
| Normal                    |  | Cold    |
| PRODUCT RECOMMENDATION 1  |  |         |
| <b>Gear Oil Alcat 10W</b> |  |         |

*Check every 10 hours, change every 6 months/ 1000 hours*

**HYDRAULIC SYSTEM**

Capacity: 64,6 liter (Hydraulic tank)

| USE                           |                          | CLIMATE  |
|-------------------------------|--------------------------|----------|
| Normal                        |                          | Tropical |
| PRODUCT RECOMMENDATION 1      | PRODUCT RECOMMENDATION 2 |          |
| <b>Agridiesel CRD+ 15W-40</b> | <b>Gear Oil Alcat 30</b> |          |

*Check every 100 hours, change every 12 months/ 2000 hours*

| USE                       |                           | CLIMATE  |
|---------------------------|---------------------------|----------|
| Normal                    |                           | Moderate |
| PRODUCT RECOMMENDATION 1  | PRODUCT RECOMMENDATION 2  |          |
| <b>Gear Oil Alcat 10W</b> | <b>Perlus Biosynth 46</b> |          |

*Check every 100 hours, change every 12 months/ 2000 hours*

**WHEEL SPINDLE BEARING FRONT**

Capacity: 0,5 liter (each wheel)

| USE                      |                          | CLIMATE       |
|--------------------------|--------------------------|---------------|
| Normal                   |                          | Mediterranean |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |               |
| <b>Gear Oil Alcat 30</b> | <b>Gear Oil Alcat 50</b> |               |

*Check every 3 months/ 500 hours, change every 24 months/ 2000 hours*

| USE                       |  | CLIMATE  |
|---------------------------|--|----------|
| Normal                    |  | Moderate |
| PRODUCT RECOMMENDATION 1  |  |          |
| <b>Gear Oil Alcat 10W</b> |  |          |

*Check every 3 months/ 500 hours, change every 24 months/ 2000 hours*

# CATERPILLAR MOTOR GRADERS 120M B9N

## (2005 AND AFTER)



### COOLING SYSTEM

Capacity: 33 liter

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>Coolant SP 17</b>     |  |          |

*Check every 10 hours, change every 72 months/ 12000 hours*

### CIRCLE DRIVE GEARBOX

Capacity: 7,2 liter

| USE                          |                                     | CLIMATE       |
|------------------------------|-------------------------------------|---------------|
| Normal                       |                                     | Mediterranean |
| PRODUCT RECOMMENDATION 1     | PRODUCT RECOMMENDATION 2            |               |
| <b>Gearlube GL-5 85W-140</b> | <b>Unigear LS GL-3/GL-5 85W-140</b> |               |

*Check every 1 months/ 100 hours, change every 24 months/ 2000 hours*

| USE                            |                          | CLIMATE                   |
|--------------------------------|--------------------------|---------------------------|
| Normal                         |                          | Moderate                  |
| PRODUCT RECOMMENDATION 1       | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3  |
| <b>Gearlube Racing 75W-140</b> | <b>SP Gear 1011</b>      | <b>Syngear TDL 75W-90</b> |

*Check every 1 months/ 100 hours, change every 24 months/ 2000 hours*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*