## **CATERPILLAR MOTOR GRADERS 130G 11W**



(1974-2001)

| ENGINE 3304<br>Capacity: 19 liter |                          |                          |
|-----------------------------------|--------------------------|--------------------------|
| USE                               |                          | CLIMATE                  |
| Normal                            |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1          | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agridiesel CRD+ 15W-40            | Dieselfleet CD+ 15W-40   | Multifleet SHPD 15W-40   |

Check every 10 hours, change every 1 months/ 250 hours

| TRANSMISSION Capacity: 79 liter    |                                  |               |
|------------------------------------|----------------------------------|---------------|
| USE                                |                                  | CLIMATE       |
| Normal                             |                                  | Mediterranean |
| PRODUCT RECOMMENDATION 1           | PRODUCT RECOMMENDATION 2         |               |
| Gear Oil Alcat 30                  | Gear Oil Alcat 50                |               |
| Check every 1 months/ 250 hours, o | change every 3 months/ 500 hours |               |
| USE                                |                                  | CLIMATE       |
| Normal                             |                                  | Arctic        |
| PRODUCT RECOMMENDATION 1           |                                  |               |
| Gear Oil Alcat 10W                 |                                  |               |
| Check every 1 months/ 250 hours, o | change every 3 months/ 500 hours |               |

| HYDRAULIC SYSTEM Capacity: 68 liter (Hydraulic tank)      |          |  |
|---|----------|--|
| USE   | CLIMATE  |  |
| Normal  | Moderate |  |
| PRODUCT RECOMMENDATION 1                                  |          |  |
| Gear Oil Alcat 10W  |          |  |
| Check every 100 hours, change every 12 months/ 2000 hours |          |  |

| GREASE POINTS/NIPPLES    |          |
|--------------------------|----------|
| USE                      | CLIMATE  |
| Normal                   | Moderate |
| PRODUCT RECOMMENDATION 1 |          |
| MoS2 Grease EP 2         |          |
|                          |          |

## **CATERPILLAR MOTOR GRADERS 130G 11W**



(1974-2001)

| COOLING SYSTEM Capacity: 38 liter |                          |                          |
|-----------------------------------|--------------------------|--------------------------|
| USE                               |                          | CLIMATE                  |
| Normal                            |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1          | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Coolant SP 15+                    | Coolant SP 12            | Coolant -38 Organic NF   |
| 011                               |                          |                          |

Check every 10 hours, change every 2000 hours/ 12 months

| CIRCLE DRIVE UNIT Capacity: 7,6 liter |               |
|---------------------------------------|---------------|
| USE                                   | CLIMATE       |
| Normal                                | Mediterranean |
| PRODUCT RECOMMENDATION 1              |               |
| Gear Oil Alcat 50                     |               |
| Change every 2000 hours/ 12 months    |               |
| USE                                   | CLIMATE       |
| Normal                                | Moderate      |
| PRODUCT RECOMMENDATION 1              |               |
| Gear Oil Alcat 30                     |               |
| Change every 2000 hours/ 12 months    |               |
| USE                                   | CLIMATE       |
| Normal                                | Arctic        |
| PRODUCT RECOMMENDATION 1              |               |
| Gear Oil Alcat 10W                    |               |
| Change every 2000 hours/ 12 months    |               |

## CATERPILLAR MOTOR GRADERS 130G 11W (1974-2001)



| USE                                     |                               | CLIMATE       |
|---|-------------------------------|---------------|
| Normal                                  |                               | Mediterranean |
| PRODUCT RECOMMENDATION 1                |                               |               |
| Gear Oil Alcat 50                       |                               |               |
| Check every 1 months/ 250 hours, change | e every 12 months/ 2000 hours |               |
| USE                                     |                               | CLIMATE       |
| Normal                                  |                               | Moderate      |
| PRODUCT RECOMMENDATION 1                |                               |               |
| Gear Oil Alcat 30                       |                               |               |
| Check every 1 months/ 250 hours, change | e every 12 months/ 2000 hours |               |
| USE                                     |                               | CLIMATE       |
| Normal                                  |                               | Arctic        |
| PRODUCT RECOMMENDATION 1                |                               |               |
| Gear Oil Alcat 10W                      |                               |               |
| Check every 1 months/ 250 hours, change | e every 12 months/ 2000 hours |               |
|   |                               |               |
| WHEEL SPINDLE HOUSINGS FRONT            |                               |               |
| Capacity: 0,5 liter (each side)         |                               |               |
| LISE                                    |                               | CLIMATE       |

| USE                                     |                              | CLIMATE       |
|---|------------------------------|---------------|
| Normal                                  |                              | Mediterranean |
| PRODUCT RECOMMENDATION 1                |                              |               |
| Gear Oil Alcat 50                       |                              |               |
| Check every 3 months/ 500 hours, change | e every 6 months/ 1000 hours |               |
| USE                                     |                              | CLIMATE       |
| Normal                                  |                              | Moderate      |
| PRODUCT RECOMMENDATION 1                |                              |               |
| Gear Oil Alcat 30                       |                              |               |
| Check every 3 months/ 500 hours, change | e every 6 months/ 1000 hours |               |
| USE                                     |                              | CLIMATE       |
| Normal                                  |                              | Arctic        |
| PRODUCT RECOMMENDATION 1                |                              |               |
| Gear Oil Alcat 10W                      |                              |               |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

Check every 3 months/ 500 hours, change every 6 months/ 1000 hours