

<b>ENGINE</b> 3054C DIT Capacity: 7,6 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agridiesel MSP 15W-40	Dieselfleet MSP 15W-40	

Check every 10 hours, change every 3 months/ 500 hours

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Armado Synth MSP 5W-40	Dieselfleet LSP Ultra 10W-30	Dieselfleet MSP 10W-30

Check every 10 hours, change every 3 months/ 500 hours

USE		CLIMATE
Alternative (acceptable)		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agrisynth MSP 10W-40	Dieselfleet MSP 15W-40	

Check every 10 hours, change every 3 months/ 500 hours

Agrisynth LSP Ultra 10W-40	Agridiesel MSP 15W-40	Armado Synth LSP Ultra 10W-40
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Alternative (acceptable)		Moderate
USE		CLIMATE

Check every 10 hours, change every 3 months/ 500 hours



Capacity: 11 liter, Capacity: 14 liter (+ equal)	al sized tires)	
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 50		
Check every 1 months/ 250 hours, change	every 6 months/ 1000 hours	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		
Check every 1 months/250 hours, change	every 6 months/ 1000 hours	
USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		
Check every 1 months/250 hours, change	every 6 months/ 1000 hours	

#### DIFFERENTIAL REAR

Capacity: 16,5 liter, Capacity: 0,5 liter (special additive)

We are unable to give a standard recommendation for this component. Please contact our service department.

#### **DIFFERENTIAL REAR STEERABLE AXLE**

Capacity: 16 liter, Capacity: 0,5 liter (special additive)

We are unable to give a standard recommendation for this component. Please contact our service department.



FINAL DRIVES FRONT		
Capacity: 0,7 liter (each side)		
use Normal		CLIMATE Mediterranean
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 50		
Check every 1 months/ 250 hours, change	every 6 months/ 1000 hours	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		
Check every 1 months/ 250 hours, change	every 6 months/ 1000 hours	
USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		
Check every 1 months/ 250 hours, change	every 6 months/ 1000 hours	
FINAL DRIVES REAR Capacity: 1,7 liter (each side)		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 50		
Check every 1 months/ 250 hours, change	every 6 months/ 1000 hours	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		
Check every 1 months/ 250 hours, change	every 6 months/ 1000 hours	
USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1  Gear Oil Alcat 10W		
Check every 1 months/ 250 hours, change	every 6 months/ 1000 hours	



TRANSMISSION Capacity: 18,5 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Gear Oil Alcat 30	Gear Oil Alcat 50		
Check every 10 hours, change every 6 mg	onths/ 1000 hours		
USE		CLIMATE	
Normal		Arctic	
PRODUCT RECOMMENDATION 1			
Gear Oil Alcat 10W			
Check every 10 hours, change every 6 mg	onths/ 1000 hours		

TRANSMISSION Powershift Capacity: 19 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gear Oil Alcat 30	Gear Oil Alcat 50	
Check every 10 hours, change ever	y 6 months/ 1000 hours	
USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		

Moderate
/ 12 months
CLIMATE
Moderate

**HYDRAULIC SYSTEM** 

Check every 10 hours, change every 6 months/ 1000 hours

Capacity: 79-99 liter, Capacity: 40 liter (Hydraulic tank)



GREASE POINTS/NIPPLES			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
MoS2 Grease EP 2			
USE		CLIMATE	
use Light Duty		climate Moderate	
	PRODUCT RECOMMENDATION 2		
Light Duty	PRODUCT RECOMMENDATION 2  Labora Grease		

COOLING SYSTEM Capacity: 19,5-25,3 liter	
use Normal	climate Moderate
PRODUCT RECOMMENDATION 1	Moderate
Coolant SP 17	

Check every 10 hours, change every 36 months/ 6000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.