

# CATERPILLAR WHEELED DOZERS 814

## (TILL 1982)



ENGINE		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agridiesel CRD+ 15W-40</b>	<b>Synfleet SHPD 10W-40</b>	<b>Dieselfleet CD+ 15W-40</b>
<i>Change every 250 hours</i>		

DIFFERENTIAL		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gear Oil Alcat 30</b>	<b>Gear Oil Alcat 50</b>	
<i>Check every 500 hours, change every 2000 hours</i>		

USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
<b>Gear Oil Alcat 10W</b>		
<i>Check every 500 hours, change every 2000 hours</i>		

FINAL DRIVES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gear Oil Alcat 30</b>	<b>Gear Oil Alcat 50</b>	
<i>Check every 500 hours, change every 2000 hours</i>		

USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
<b>Gear Oil Alcat 10W</b>		
<i>Check every 500 hours, change every 2000 hours</i>		

# CATERPILLAR WHEELED DOZERS 814 (TILL 1982)



## TRANSMISSION Powershift

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gear Oil Alcat 30</b>	<b>Gear Oil Alcat 50</b>	

*Check every 500 hours, change every 1000 hours*

USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		
<b>Gear Oil Alcat 10W</b>		

*Check every 500 hours, change every 1000 hours*

## HYDRAULIC SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agridiesel CRD+ 15W-40</b>	<b>Kroontrak MTH 10W-30</b>	<b>Synfleet SHPD 10W-40</b>

*Check every 500 hours, change every 2000 hours*

## GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>MoS2 Grease EP 2</b>		

## STEERING GEAR SHAFT LOWER BEARING

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gear Oil Alcat 30</b>	<b>Gear Oil Alcat 50</b>	

USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
<b>Gear Oil Alcat 10W</b>		

# CATERPILLAR WHEELED DOZERS 814 (TILL 1982)



## STEERING GEAR UNIT

USE		CLIMATE
Normal		Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gear Oil Alcat 30</b>	<b>Gear Oil Alcat 50</b>	

USE		CLIMATE
Normal		Arctic

PRODUCT RECOMMENDATION 1		
<b>Gear Oil Alcat 10W</b>		

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*