

# JCB SKID STEER LOADERS ROBOT 1110

## JCB 444 TIER 3 (2008 AND AFTER)

**ENGINE JCB 444**

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agridiesel CRD+ 15W-40</b>	<b>Dieselfleet CD+ 15W-40</b>	<b>Multifleet SHPD 15W-40</b>

*Change every 500 hours*

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Synfleet SHPD 10W-40</b>	<b>Multifleet SHPD 10W-40</b>	

*Change every 500 hours*

USE		CLIMATE
Severe		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agridiesel CRD+ 15W-40</b>	<b>Dieselfleet CD+ 15W-40</b>	<b>Multifleet SHPD 15W-40</b>

*Change every 250 hours*

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Synfleet SHPD 10W-40</b>	<b>Multifleet SHPD 10W-40</b>	

*Change every 250 hours*

**HYDRAULIC SYSTEM**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Synfleet SHPD 10W-40</b>	<b>Multifleet SHPD 10W-40</b>	

*Change every 2000 hours/ 24 months*

**GREASE POINTS/NIPPLES**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>HT Q9 High Grade Grease</b>	<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>

# JCB SKID STEER LOADERS ROBOT 1110

## JCB 444 TIER 3 (2008 AND AFTER)



### COOLING SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant -38 Organic NF</b>	<b>Coolant -26</b>	

### CHAIN CASE

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agridiesel CRD+ 15W-40</b>	<b>Dieselfleet CD+ 15W-40</b>	<b>Multifleet SHPD 15W-40</b>

*Change every 2000 hours/ 24 months*

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Synfleet SHPD 10W-40</b>	<b>Multifleet SHPD 10W-40</b>	

*Change every 2000 hours/ 24 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*