

# JCB WHEELED LOADERS 416 HT JCB 444 (2007-2013)



**ENGINE** JCB 444  
Capacity: 11,5 liter

**USE**  
Normal

**CLIMATE**  
Mediterranean

**PRODUCT RECOMMENDATION 1**  
**Agridiesel MSP 15W-40**

**PRODUCT RECOMMENDATION 2**  
**Agridiesel CRD+ 15W-40**

**PRODUCT RECOMMENDATION 3**  
**Dieselfleet CD+ 15W-40**

**DIFFERENTIAL FRONT** JCB PD87  
Capacity: 25 liter

**USE**  
Normal

**CLIMATE**  
Moderate

**PRODUCT RECOMMENDATION 1**  
**Agrifluid HT-Plus**

**PRODUCT RECOMMENDATION 2**  
**Agrifluid HT**

**DIFFERENTIAL FRONT** JCB PD90  
Capacity: 25 liter

**USE**  
Normal

**CLIMATE**  
Moderate

**PRODUCT RECOMMENDATION 1**  
**Agrifluid HT-Plus**

**PRODUCT RECOMMENDATION 2**  
**Agrifluid HT**

**DIFFERENTIAL REAR** JCB PD87  
Capacity: 25 liter

**USE**  
Normal

**CLIMATE**  
Moderate

**PRODUCT RECOMMENDATION 1**  
**Agrifluid HT-Plus**

**PRODUCT RECOMMENDATION 2**  
**Agrifluid HT**

**DIFFERENTIAL REAR** JCB PD90  
Capacity: 25 liter

**USE**  
Normal

**CLIMATE**  
Moderate

**PRODUCT RECOMMENDATION 1**  
**Agrifluid HT-Plus**

**PRODUCT RECOMMENDATION 2**  
**Agrifluid HT**

# JCB WHEELED LOADERS 416 HT JCB 444 (2007-2013)

**TRANSMISSION** ZF 4WG115 4/3

Capacity: 27 liter

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**SP Matic 2032****HYDRAULIC SYSTEM**

Capacity: 125 liter

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Perlus H 32****GREASE POINTS/NIPPLES**

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**HT Q9 High Grade Grease****COOLING SYSTEM**

Capacity: 23 liter

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Coolant SP 15+**

## PRODUCT RECOMMENDATION 2

**Coolant SP 12**

## PRODUCT RECOMMENDATION 3

**Coolant -38 Organic NF**

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.