

JCB WHEELED LOADERS 436 STAGE II/T2

(1305000->1409999) (2004-2008)



ENGINE Cummins 6BTAA5.9C
Capacity: 14 liter

USE
Normal

CLIMATE
Mediterranean

PRODUCT RECOMMENDATION 1

Agridiesel MSP 15W-40

PRODUCT RECOMMENDATION 2

Agridiesel CRD+ 15W-40

PRODUCT RECOMMENDATION 3

Dieselfleet CD+ 15W-40

Check every 10 hours, change every 500 hours/ 6 months

DIFFERENTIAL FRONT Graziano PR12
Capacity: 39 liter (+ hub reductions)

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90

Check every 3 months/ 250 hours, change every 12 months/ 1000 hours

DIFFERENTIAL REAR Graziano PR12
Capacity: 39 liter (+ hub reductions)

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90

Check every 3 months/ 250 hours, change every 12 months/ 1000 hours

JCB WHEELED LOADERS 436 STAGE II/T2

(1305000->1409999) (2004-2008)

**TRANSMISSION** ZF 4WG190 4/3

Capacity: 32,5 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1
Multifleet SCD 20W-20

Check every 3 months/ 250 hours, change every 12 months/ 1000 hours

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1
Agrifluid Synth XHP Ultra

PRODUCT RECOMMENDATION 2
Agrifluid HT-Plus

PRODUCT RECOMMENDATION 3
Agrifluid HT

Check every 3 months/ 250 hours, change every 12 months/ 1000 hours

USE	CLIMATE
Initial service	Mediterranean

PRODUCT RECOMMENDATION 1
Multifleet SCD 20W-20

Change every 100 hours

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1
Agrifluid Synth XHP Ultra

PRODUCT RECOMMENDATION 2
Agrifluid HT-Plus

PRODUCT RECOMMENDATION 3
Agrifluid HT

Change every 100 hours

HYDRAULIC SYSTEM

Capacity: 210 liter

USE	CLIMATE
Flexible (max)	Moderate

PRODUCT RECOMMENDATION 1
Perlus Biosynth 46

PRODUCT RECOMMENDATION 2
Perlus H 46

Check every 10 hours, change every 2000 hours/ 24 months

USE	CLIMATE
Flexible, fluid analysis	Moderate

PRODUCT RECOMMENDATION 1
Perlus Biosynth 46

PRODUCT RECOMMENDATION 2
Perlus H 46

Check every 3 months/ 250 hours

JCB WHEELED LOADERS 436 STAGE II/T2

(1305000->1409999) (2004-2008)



GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
HT Q9 High Grade Grease		

COOLING SYSTEM

Capacity: 35 liter

USE		CLIMATE
Flexible (max)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Check every 6 months/ 500 hours, change every 24 months/ 2000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.