PRODUCT RECOMMENDATION

JCB WHEELED LOADERS 467 ZX QSM11 STAGE IIIA/T3 (2014 AND AFTER)

ENGINE QSM11
Capacity: 41 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel MSP 15W-40	**Agridiesel CRD+ 15W-40**	**Dieselfleet CD+ 15W-40**

Check every 10 hours, change every 500 hours/ 6 months

DIFFERENTIAL FRONT ZF MT-L3105-II
Capacity: 42 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Agrifluid HT		

Check every 6 months/ 500 hours, change every 18 months/ 1500 hours

DIFFERENTIAL REAR ZF MT-L3105-II
Capacity: 42 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Agrifluid HT		

Check every 6 months/ 500 hours, change every 18 months/ 1500 hours

TRANSMISSION ZF 4WG260 4/3
Capacity: 42 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
SP Matic 2032		

Check every 10 hours, change every 1000 hours/ 12 months

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1		
SP Matic 2032		

Change every 100 hours

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

JCB WHEELED LOADERS 467 ZX QSM11 STAGE IIIA/T3 (2014 AND AFTER)

TRANSMISSION ZF 5WG260
Capacity: 42 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
SP Matic 2032		

Check every 10 hours, change every 1000 hours/ 12 months

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1		
SP Matic 2032		

Change every 100 hours

HYDRAULIC SYSTEM
Capacity: 170 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus Biosynth 46	**Perlus H 46**	

Check every 10 hours, change every 24 months/ 4000 hours

GREASE POINTS/NIPPLES

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
HT Q9 High Grade Grease	**Labora Grease**	

GREASE POINTS/NIPPLES CENTRAL LUBRICATION SYSTEM

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	**Q5 MP Calcep Grease EP 2**	**MP Lithep Grease EP 2**

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

JCB WHEELED LOADERS 467 ZX QSM11 STAGE IIIA/T3 (2014 AND AFTER)

COOLING SYSTEM Capacity: 39 liter		
USE Normal		CLIMATE Moderate
PRODUCT RECOMMENDATION 1 **Coolant SP 15+**	PRODUCT RECOMMENDATION 2 **Coolant SP 12**	PRODUCT RECOMMENDATION 3 **Coolant -38 Organic NF**
Check every 10 hours, change every 18 months/ 3000 hours		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367