

# JCB TRACKED EXCAVATORS 8008 CTS STAGE IIIA/T3 (M1239500 ->) (2006-2010)



**ENGINE** Perkins 403C-07  
Capacity: 3,5 liter

USE  
Normal

CLIMATE  
Mediterranean

PRODUCT RECOMMENDATION 1  
**Dieselfleet CD+ 15W-40**

PRODUCT RECOMMENDATION 2  
**Multifleet SHPD 15W-40**

*Check every 10 hours, change every 3 months/ 500 hours*

## HYDRAULIC SYSTEM

Capacity: 16 liter (Hydraulic tank), Capacity: 21 liter (System)

USE  
Normal

CLIMATE  
Moderate

PRODUCT RECOMMENDATION 1  
**Perlus H 46**

PRODUCT RECOMMENDATION 2  
**Perlus AF 46**

*Check every 10 hours, change every 2000 hours/ 24 months*

## GREASE POINTS/NIPPLES OTHERS

USE  
Normal

CLIMATE  
Moderate

PRODUCT RECOMMENDATION 1  
**Labora Grease**

PRODUCT RECOMMENDATION 2  
**Q5 MP Calcep Grease EP 2**

PRODUCT RECOMMENDATION 3  
**MP Lithep Grease EP 2**

*Check every 10 hours*

## COOLING SYSTEM

Capacity: 4,5 liter

USE  
Normal

CLIMATE  
Moderate

PRODUCT RECOMMENDATION 1  
**Coolant SP 15+**

PRODUCT RECOMMENDATION 2  
**Coolant SP 12**

PRODUCT RECOMMENDATION 3  
**Coolant -38 Organic NF**

*Check every 10 hours, change every 2000 hours/ 24 months*

## SWING RING BEARINGS

USE  
Normal

CLIMATE  
Moderate

PRODUCT RECOMMENDATION 1  
**Labora Grease**

PRODUCT RECOMMENDATION 2  
**Q5 MP Calcep Grease EP 2**

PRODUCT RECOMMENDATION 3  
**MP Lithep Grease EP 2**

*Check every 50 hours*

# JCB TRACKED EXCAVATORS 8008 CTS STAGE IIIA/T3 (M1239500 ->) (2006-2010)



## SWING RING GEAR TEETH

We are unable to give a standard recommendation for this component. Please contact our service department.

## TRAVEL REDUCTION UNIT

Capacity: 0,3 liter (each)

### USE

Normal

### CLIMATE

Moderate

### PRODUCT RECOMMENDATION 1

**Multifleet SCD 30**

*Check every 1 months/ 250 hours, change every 3 months/ 500 hours*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*