

# JCB TRACKED EXCAVATORS 8014 CTS STAGE IIIA/T3 (1156000->)(2012 AND AFTER)



**ENGINE** Perkins 403D-11  
Capacity: 4 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Kroontrak MTH 10W-30</b>	<b>Synfleet SHPD 10W-40</b>	<b>Multifleet SHPD 10W-40</b>

*Check every 10 hours, change every 500 hours/ 6 months*

**HYDRAULIC SYSTEM**  
Capacity: 30 liter

USE		CLIMATE
Normal		Tropical
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Perlus H 46</b>	<b>Perlus AF 46</b>	

*Check every 10 hours, change every 2000 hours/ 24 months*

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Perlus H 32</b>	<b>Perlus AF 32</b>	

*Check every 10 hours, change every 2000 hours/ 24 months*

## GREASE POINTS/NIPPLES OTHERS

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>

**COOLING SYSTEM**  
Capacity: 4,5-5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Coolant SP 15+</b>	<b>Coolant SP 12</b>	<b>Coolant -38 Organic NF</b>

*Check every 10 hours, change every 2000 hours/ 24 months*

## SWING RING GEAR TEETH

We are unable to give a standard recommendation for this component. Please contact our service department.

# JCB TRACKED EXCAVATORS 8014 CTS STAGE IIIA/T3 (1156000->) (2012 AND AFTER)



## SWING RING BEARINGS

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>

*Check every 50 hours*

## TRACK IDLERS

Capacity: 0,03 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gearlube GL-5 80W-90</b>	<b>Unigear HS GL-3/GL-5 80W-90</b>	

*Change every 1000 hours/ 12 months*

## TRACK ROLLERS

Capacity: 0,03 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gearlube GL-5 80W-90</b>	<b>Unigear HS GL-3/GL-5 80W-90</b>	

*Change every 1000 hours/ 12 months*

## TRAVEL REDUCTION UNIT

Capacity: 0,3 liter (each)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Multifleet SCD 30</b>		

*Change every 6 months/ 500 hours*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.