PRODUCT RECOMMENDATION

JCB TRACKED EXCAVATORS JS-210 LC STAGE IIIA/T3 (1610000->1612499) (2011-2014)

ENGINE Isuzu 4HK1X
Capacity: 23,5 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel MSP 15W-40	**Agridiesel CRD+ 15W-40**	**Dieselfleet CD+ 15W-40**

Check every 10 hours, change every 3 months/ 500 hours

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agrisynth LSP 10W-40	**Armado Synth 10W-40**	

Check every 10 hours, change every 3 months/ 500 hours

HYDRAULIC SYSTEM
Capacity: 200 liter, Capacity: 120 liter (Hydraulic tank)

USE		CLIMATE
Flexible (max)		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Perlus H 46	**Perlus H 68**	**Perlus AF 46**

Check every 10 hours, change every 30 months/ 5000 hours

USE		CLIMATE
Flexible (max)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus H 32	**Perlus AF 32**	

Check every 10 hours, change every 30 months/ 5000 hours

USE		CLIMATE
Flexible, fluid analysis		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Perlus H 46	**Perlus H 68**	**Perlus AF 46**

Check every 3 months/ 500 hours

USE		CLIMATE
Flexible, fluid analysis		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus H 32	**Perlus AF 32**	

Check every 3 months/ 500 hours

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

JCB TRACKED EXCAVATORS JS-210 LC STAGE IIIA/T3 (1610000->1612499) (2011-2014)

GREASE POINTS/NIPPLES OTHERS

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
HT Q9 High Grade Grease		

Check every 50 hours

GREASE POINTS/NIPPLES RECOIL SPRING CYLINDER

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
HT Q9 High Grade Grease		

COOLING SYSTEM
Capacity: 28 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	**Coolant SP 12**	**Coolant -38 Organic NF**

Check every 10 hours, change every 24 months/ 4000 hours

SWING REDUCTION UNIT
Capacity: 5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	**Unigear HS GL-3/GL-5 80W-90**	

Check every 1 months/ 250 hours, change every 6 months/ 1000 hours

SWING RING GEAR TEETH
Capacity: 17 kg

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
HT Q9 High Grade Grease		

Check every 3 months/ 500 hours

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

JCB TRACKED EXCAVATORS JS-210 LC STAGE IIIA/T3 (1610000->1612499) (2011-2014)

SWING RING BEARINGS

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
HT Q9 High Grade Grease		

Check every 1 months/ 250 hours

TRACK IDLERS

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
Gearlube GL-5 80W-90	**Unigear HS GL-3/GL-5 80W-90**	

TRACK ROLLERS

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
Gearlube GL-5 80W-90	**Unigear HS GL-3/GL-5 80W-90**	

TRAVEL REDUCTION UNIT

Capacity: 4,7 liter (each)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
Gearlube GL-5 80W-90	**Unigear HS GL-3/GL-5 80W-90**	

Check every 1 months/ 250 hours, change every 6 months/ 1000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367