JCB TELESCOPIC HANDLERS 520-40 PERKINS 404D-22 STAGE IIIA / TIER 3 (2004



AND AFTER)

| ENGINE Perkins 404D-22 Capacity: 10,5 liter | | |
|--|--------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agridiesel CRD+ 15W-40 | Dieselfleet CD+ 15W-40 | Multifleet SHPD 15W-40 |

| DIFFERENTIAL FRONT Capacity: 5 liter | | | |
|---|-----------------------------|----------|--|
| USE | | CLIMATE | |
| Normal | | Moderate | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | | |
| Gearlube GL-5 80W-90 | Unigear HS GL-3/GL-5 80W-90 | | |

| DIFFERENTIAL REAR Capacity: 5 liter | | |
|--|-----------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gearlube GL-5 80W-90 | Unigear HS GL-3/GL-5 80W-90 | |

| HUB REDUCTIONS FRONT Capacity: 0,5 liter | | |
|---|-----------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gearlube GL-5 80W-90 | Unigear HS GL-3/GL-5 80W-90 | |

| HUB REDUCTIONS REAR Capacity: 0,5 liter | | | |
|--|-----------------------------|----------|--|
| USE | | CLIMATE | |
| Normal | | Moderate | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | | |
| Gearlube GL-5 80W-90 | Unigear HS GL-3/GL-5 80W-90 | | |

JCB TELESCOPIC HANDLERS 520-40 PERKINS 404D-22 STAGE IIIA / TIER 3 (2004



AND AFTER)

| TRANSFERBOX Capacity: 0,75 liter | | |
|-------------------------------------|-----------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gearlube GL-5 80W-90 | Unigear HS GL-3/GL-5 80W-90 | |

| HYDRAULIC SYSTEM Capacity: 68 liter (Hydraulic tank) | | |
|--|--------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Synfleet SHPD 10W-40 | Armado Synth 5W-30 | Multifleet SHPD 10W-40 |

| HYDRAULIC BRAKE SYSTEM | |
|--------------------------|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Perlus H 15 | |

| GREASE POINTS/NIPPLES | | |
|--------------------------|--------------------------|--------------------------|
| USE | | CLIMATE |
| Preferred, extended | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| HT Q9 High Grade Grease | | |
| USE | | CLIMATE |
| Alternative (acceptable) | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 |

| COOLING SYSTEM Capacity: 8 liter | | |
|----------------------------------|--------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Coolant SP 15+ | Coolant SP 12 | Coolant -38 Organic NF |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the

PRODUCT RECOMMENDATION

JCB TELESCOPIC HANDLERS 520-40 PERKINS 404D-22 STAGE IIIA / TIER 3 (2004 AND AFTER)



information contained herein is subject to changes without notification.