

JCB TELESCOPIC HANDLERS 528S

**ENGINE**

Capacity: 10 liter

USE

Normal

CLIMATE

Mediterranean

PRODUCT RECOMMENDATION 1

Agridiesel CRD+ 15W-40

PRODUCT RECOMMENDATION 2

Dieselfleet CD+ 15W-40

PRODUCT RECOMMENDATION 3

Multifleet SHPD 15W-40

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Synfleet SHPD 10W-40

PRODUCT RECOMMENDATION 2

Multifleet SHPD 10W-40**DIFFERENTIAL FRONT**

Capacity: 9 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Agrifluid HT**DIFFERENTIAL REAR**

Capacity: 8,4 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Agrifluid HT**HUB REDUCTIONS FRONT**

Capacity: 2 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Agrifluid HT

JCB TELESCOPIC HANDLERS 528S

**HUB REDUCTIONS REAR**

Capacity: 2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid HT		

TRANSMISSION SynchroShuttle

Capacity: 17 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
ATF-F (Ford)		

HYDRAULIC SYSTEM

Capacity: 110 liter

USE		CLIMATE
Normal		Tropical
PRODUCT RECOMMENDATION 1		
Perlus H 46		

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Perlus H 32		

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
HT Q9 High Grade Grease	Labora Grease	

COOLING SYSTEM

Capacity: 20 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or

JCB TELESCOPIC HANDLERS 528S



inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.