JCB TELESCOPIC HANDLERS 536-60 (93 KW) STAGE IIIB/T4I (2012 AND AFTER)



ENGINE JCB Ecomax T4i Capacity: 15 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

DIFFERENTIAL FRONT Capacity: 17,7 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Agrifluid HT	

Check every 50 hours, change every 6 months/ 500 hours

DIFFERENTIAL REAR Capacity: 10 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid HT		
Check every 50 hours, change every 6 months/ 500 hours		

HUB REDUCTIONS FRONT Capacity: 1,9 liter (each hub)	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Agrifluid HT	
Change every 6 months/ 500 hours	

HUB REDUCTIONS REAR Capacity: 2 liter (each hub)	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Agrifluid HT	
Change every 6 months/ 500 hours	

JCB TELESCOPIC HANDLERS 536-60 (93 KW) STAGE IIIB/T4I (2012 AND AFTER)



Capacity: 23 liter (Dry fill), Capacity: 21 lite	r (Service fill)	
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		
Check every 10 hours, change every 1000	hours/ 12 months	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		
<u> </u>		

Check every 10 hours, change every 1000 hours/ 12 months

HYDRAULIC SYSTEM Capacity: 115 liter (Hydraulic tank)		
USE		CLIMATE
Normal		Tropical
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus H 46	Perlus AF 46	

Check every 50 hours, change every 2000 hours/24 months

Perlus H 32	Perlus AF 32	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Normal		Moderate
USE		CLIMATE

Check every 50 hours, change every 2000 hours/24 months

HYDRAULIC BRAKE SYSTEM		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Perlus H 15		
Check eveny 10 hours change eveny 2000	hours/24 months	

Check every 10 hours, change every 2000 hours/ 24 months

GREASE POINTS/NIPPLES		
USE		CLIMATE
Preferred		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
HT Q9 High Grade Grease	Labora Grease	

JCB TELESCOPIC HANDLERS 536-60 (93 KW) STAGE IIIB/T4I (2012 AND AFTER)



COOLING SYSTEM Capacity: 28 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Check every 10 hours, change every 2000 hours/24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.