

# KUBOTA TRACKED EXCAVATORS

## K/KH/KX/U KH191

**ENGINE** Kubota

## USE

Normal

## CLIMATE

Mediterranean

## PRODUCT RECOMMENDATION 1

**Multifleet SCD 30***Change every 100 hours*

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Dieselfleet CD+ 15W-40**

## PRODUCT RECOMMENDATION 2

**Multifleet SHPD 15W-40***Change every 100 hours*

## USE

Normal

## CLIMATE

Cold

## PRODUCT RECOMMENDATION 1

**Kroontrak MTH 10W-30**

## PRODUCT RECOMMENDATION 2

**Synfleet SHPD 10W-40**

## PRODUCT RECOMMENDATION 3

**Multifleet SHPD 10W-40***Change every 100 hours*

## USE

Initial service

## CLIMATE

Mediterranean

## PRODUCT RECOMMENDATION 1

**Multifleet SCD 30***Change every 35 hours*

## USE

Initial service

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Dieselfleet CD+ 15W-40**

## PRODUCT RECOMMENDATION 2

**Multifleet SHPD 15W-40***Change every 35 hours*

## USE

Initial service

## CLIMATE

Cold

## PRODUCT RECOMMENDATION 1

**Kroontrak MTH 10W-30**

## PRODUCT RECOMMENDATION 2

**Synfleet SHPD 10W-40**

## PRODUCT RECOMMENDATION 3

**Multifleet SHPD 10W-40***Change every 35 hours*

# KUBOTA TRACKED EXCAVATORS

## K/KH/KX/U KH191



### HYDRAULIC SYSTEM

|        |               |
|--------|---------------|
| USE    | CLIMATE       |
| Normal | Mediterranean |

|                          |  |  |
|--------------------------|--|--|
| PRODUCT RECOMMENDATION 1 |  |  |
| <b>Perlus H 68</b>       |  |  |

*Change every 1000 hours*

|        |          |
|--------|----------|
| USE    | CLIMATE  |
| Normal | Moderate |

|                          |  |  |
|--------------------------|--|--|
| PRODUCT RECOMMENDATION 1 |  |  |
| <b>Perlus H 46</b>       |  |  |

*Change every 1000 hours*

|        |         |
|--------|---------|
| USE    | CLIMATE |
| Normal | Cold    |

|                          |  |  |
|--------------------------|--|--|
| PRODUCT RECOMMENDATION 1 |  |  |
| <b>Perlus H 32</b>       |  |  |

*Change every 1000 hours*

### GREASE POINTS/NIPPLES

|        |          |
|--------|----------|
| USE    | CLIMATE  |
| Normal | Moderate |

|                          |                                 |                              |
|--------------------------|---------------------------------|------------------------------|
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2        | PRODUCT RECOMMENDATION 3     |
| <b>Labora Grease</b>     | <b>Q5 MP Calcep Grease EP 2</b> | <b>MP Lithep Grease EP 2</b> |

### SWING BEARING

|        |          |
|--------|----------|
| USE    | CLIMATE  |
| Normal | Moderate |

|                          |                                 |                              |
|--------------------------|---------------------------------|------------------------------|
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2        | PRODUCT RECOMMENDATION 3     |
| <b>Labora Grease</b>     | <b>Q5 MP Calcep Grease EP 2</b> | <b>MP Lithep Grease EP 2</b> |

### SWING GEAR TEETH

|        |          |
|--------|----------|
| USE    | CLIMATE  |
| Normal | Moderate |

|                          |                                 |                              |
|--------------------------|---------------------------------|------------------------------|
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2        | PRODUCT RECOMMENDATION 3     |
| <b>Labora Grease</b>     | <b>Q5 MP Calcep Grease EP 2</b> | <b>MP Lithep Grease EP 2</b> |

# KUBOTA TRACKED EXCAVATORS

## K/KH/KX/U KH191



### SWING REDUCTION UNIT

| USE                         |                                    | CLIMATE  |
|-----------------------------|------------------------------------|----------|
| Normal                      |                                    | Moderate |
| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2           |          |
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |          |

*Change every 1000 hours*

### TRAVEL REDUCTION UNIT

| USE                         |                                    | CLIMATE  |
|-----------------------------|------------------------------------|----------|
| Normal                      |                                    | Moderate |
| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2           |          |
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |          |

*Change every 1000 hours*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*