PRODUCT RECOMMENDATION

# KUBOTA TRACKED EXCAVATORS K/KH/KX/U KX018-4 KUBOTA D902-E-BH (S/N <- 67055) (2011-2018)

**ENGINE** Kubota D902-E
Capacity: 3,6 liter

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| **PRODUCT RECOMMENDATION 1** | **PRODUCT RECOMMENDATION 2** | **PRODUCT RECOMMENDATION 3** |
| **Kroontrak MTH 10W-30** | **Synfleet SHPD 10W-40** | **Dieselfleet LSP Ultra 10W-30** |

*Check every 10 hours, change every 500 hours*

**HYDRAULIC SYSTEM**
Capacity: 15,5 liter (Hydraulic tank), Capacity: 28 liter (Total)

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| **PRODUCT RECOMMENDATION 1** | | |
| **Perlus H 46** | | |

*Check every 10 hours, change every 1000 hours*

| USE | | CLIMATE |
|---|---|---|
| Breaker use < 40% | | Moderate |
| **PRODUCT RECOMMENDATION 1** | | |
| **Perlus H 46** | | |

*Check every 10 hours, change every 800 hours*

| USE | | CLIMATE |
|---|---|---|
| Breaker use 40 - 60% | | Moderate |
| **PRODUCT RECOMMENDATION 1** | | |
| **Perlus H 46** | | |

*Check every 10 hours, change every 400 hours*

| USE | | CLIMATE |
|---|---|---|
| Breaker use 60 - 80% | | Moderate |
| **PRODUCT RECOMMENDATION 1** | | |
| **Perlus H 46** | | |

*Check every 10 hours, change every 300 hours*

| USE | | CLIMATE |
|---|---|---|
| Breaker use > 80% | | Moderate |
| **PRODUCT RECOMMENDATION 1** | | |
| **Perlus H 46** | | |

*Check every 10 hours, change every 200 hours*

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

# KUBOTA TRACKED EXCAVATORS K/KH/KX/U KX018-4 KUBOTA D902-E-BH (S/N <- 67055) (2011-2018)

## COOLING SYSTEM
Capacity: 2,7-2,9 liter, Capacity: 0,56 liter (Reserve tank)

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|---|---|---|
| **Coolant -38 Organic NF** | **Coolant -26** | |

*Check every 10 hours, change every 24 months*

## IDLER FRONT
Capacity: 0,03 liter (each)

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|---|---|---|
| **Multifleet SCD 30** | | |

*Change every 2000 hours*

## TRACK ROLLER
Capacity: 0,04 liter (each)

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|---|---|---|
| **Multifleet SCD 30** | | |

*Change every 2000 hours*

## TRAVEL REDUCTION UNIT
Capacity: 0,33 liter (each)

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|---|---|---|
| **Agrifluid HT-Plus** | **SP Gear 5015** | **Gearlube GL-4 80W** |

*Change every 500 hours*

| USE | CLIMATE |
|---|---|
| Initial service | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|---|---|---|
| **Agrifluid HT-Plus** | **SP Gear 5015** | **Gearlube GL-4 80W** |

*Change every 50 hours*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367