PRODUCT RECOMMENDATION

KUBOTA TRACKED EXCAVATORS K/KH/KX/U KX41-3S (EU) KUBOTA D902-BH (2003-2011)

ENGINE Kubota D902-E
Capacity: 3,6 liter

USE		CLIMATE
Normal		Tropical
PRODUCT RECOMMENDATION 1		
Multifleet SCD 30		
Change every 250 hours		

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Multifleet SCD 20W-20		
Change every 250 hours		

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak MTH 10W-30	**Synfleet SHPD 10W-40**	**Dieselfleet CD+ 15W-40**
Change every 250 hours		

USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		
Change every 250 hours		

USE		CLIMATE
Initial service		Tropical
PRODUCT RECOMMENDATION 1		
Multifleet SCD 30		
Change every 50 hours		

USE		CLIMATE
Initial service		Mediterranean
PRODUCT RECOMMENDATION 1		
Multifleet SCD 20W-20		
Change every 50 hours		

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak MTH 10W-30	**Synfleet SHPD 10W-40**	**Dieselfleet CD+ 15W-40**
Change every 50 hours		

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

KUBOTA TRACKED EXCAVATORS K/KH/KX/U KX41-3S (EU) KUBOTA D902-BH (2003-2011)

USE		CLIMATE
Initial service		Arctic
PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		
Change every 50 hours		

HYDRAULIC SYSTEM
Capacity: 27 liter, Capacity: 14 liter (Hydraulic tank)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Perlus H 46		
Change every 1000 hours		

COOLING SYSTEM
Capacity: 2,7-2,9 liter, Capacity: 0,56 liter (Reserve tank)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	**Coolant -26**	
Change every 24 months		

IDLER FRONT
Capacity: 0,03 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Multifleet SCD 30		
Change every 2000 hours		

TRACK ROLLER
Capacity: 0,04 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Multifleet SCD 30		
Change every 2000 hours		

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

KUBOTA TRACKED EXCAVATORS K/KH/KX/U KX41-3S (EU) KUBOTA D902-BH (2003-2011)

TRAVEL REDUCTION UNIT
Capacity: 0,25 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	**Unigear HS GL-3/GL-5 80W-90**	

Change every 500 hours

UPPER ROLLER

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Multifleet SCD 30		

Change every 2000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367