

KUBOTA TRACKED EXCAVATORS

K/KH/KX/U KX91-2A

**ENGINE** Kubota

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Multifleet SCD 30*Change every 100 hours*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Dieselfleet CD+ 15W-40

PRODUCT RECOMMENDATION 2

Multifleet SHPD 15W-40*Change every 100 hours*

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1

Kroontrak MTH 10W-30

PRODUCT RECOMMENDATION 2

Synfleet SHPD 10W-40

PRODUCT RECOMMENDATION 3

Multifleet SHPD 10W-40*Change every 100 hours*

USE	CLIMATE
Initial service	Mediterranean

PRODUCT RECOMMENDATION 1

Multifleet SCD 30*Change every 35 hours*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

Dieselfleet CD+ 15W-40

PRODUCT RECOMMENDATION 2

Multifleet SHPD 15W-40*Change every 35 hours*

USE	CLIMATE
Initial service	Cold

PRODUCT RECOMMENDATION 1

Kroontrak MTH 10W-30

PRODUCT RECOMMENDATION 2

Synfleet SHPD 10W-40

PRODUCT RECOMMENDATION 3

Multifleet SHPD 10W-40*Change every 35 hours*

KUBOTA TRACKED EXCAVATORS

K/KH/KX/U KX91-2A



HYDRAULIC SYSTEM

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Perlus H 68*Change every 1000 hours*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Perlus H 46*Change every 1000 hours*

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1

Perlus H 32*Change every 1000 hours*

PINS + BUSHINGS

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Labora Grease

PRODUCT RECOMMENDATION 2

Q5 MP Calcep Grease EP 2

PRODUCT RECOMMENDATION 3

MP Lithep Grease EP 2

SWING REDUCTION UNIT

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 2

Unigear HS GL-3/GL-5 80W-90*Change every 1000 hours*

TRACK ROLLERS + FRONT IDLERS

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 2

Unigear HS GL-3/GL-5 80W-90

KUBOTA TRACKED EXCAVATORS

K/KH/KX/U KX91-2A

**TRAVEL REDUCTION UNIT**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Change every 1000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.