

KUBOTA TRACKED EXCAVATORS

K/KH/KX/U KX91-3 (2002-2005)



ENGINE Kubota D1503-M
Capacity: 6,6 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|-------------------------------|-------------------------------|-------------------------------|
| Agridiesel CRD+ 15W-40 | Dieselfleet CD+ 15W-40 | Multifleet SHPD 15W-40 |

Change every 250 hours

| USE | CLIMATE |
|--------|---------|
| Normal | Cold |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|------------------------------|---------------------------|--|
| Multifleet SCD 20W-20 | Multifleet SCD 10W | |

Change every 250 hours

| USE | CLIMATE |
|-----------------|----------|
| Initial service | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|-------------------------------|-------------------------------|-------------------------------|
| Agridiesel CRD+ 15W-40 | Dieselfleet CD+ 15W-40 | Multifleet SHPD 15W-40 |

Change every 50 hours

| USE | CLIMATE |
|-----------------|---------|
| Initial service | Cold |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|------------------------------|---------------------------|--|
| Multifleet SCD 20W-20 | Multifleet SCD 10W | |

Change every 50 hours

HYDRAULIC SYSTEM

Capacity: 41 liter, Capacity: 33 liter (Hydraulic tank)

| USE | CLIMATE |
|--------|---------------|
| Normal | Mediterranean |

| PRODUCT RECOMMENDATION 1 | | |
|--------------------------|--|--|
| Perlus H 68 | | |

Change every 1000 hours

| USE | CLIMATE |
|--------|---------|
| Normal | Cold |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|--------------------------|--------------------------|--|
| Perlus H 46 | Perlus H 32 | |

Change every 1000 hours

KUBOTA TRACKED EXCAVATORS

K/KH/KX/U KX91-3 (2002-2005)



GREASE POINTS/NIPPLES

| USE | | CLIMATE |
|--------------------------|---------------------------------|------------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 |

COOLING SYSTEM

Capacity: 5,6 liter

| USE | | CLIMATE |
|-------------------------------|--------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Coolant -38 Organic NF | Coolant -26 | |

Change every 24 months

TRAVEL REDUCTION UNIT

Capacity: 0,6 liter (each)

| USE | | CLIMATE |
|------------------------------|--|---------------|
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | | |
| Gearlube GL-5 85W-140 | | |

Change every 500 hours

| USE | | CLIMATE |
|-----------------------------|------------------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gearlube GL-5 80W-90 | Unigear HS GL-3/GL-5 80W-90 | |

Change every 500 hours

| USE | | CLIMATE |
|--------------------------|--------------------------|--------------------------|
| Normal | | Cold |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| SP Gear 1081 | SP Gear 5015 | SP Gear 1071 |

Change every 500 hours

| USE | | CLIMATE |
|------------------------------|--|---------------|
| Initial service | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | | |
| Gearlube GL-5 85W-140 | | |

Change every 50 hours

KUBOTA TRACKED EXCAVATORS

K/KH/KX/U KX91-3 (2002-2005)



| USE | | CLIMATE |
|-----------------------------|------------------------------------|----------|
| Initial service | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gearlube GL-5 80W-90 | Unigear HS GL-3/GL-5 80W-90 | |

Change every 50 hours

| USE | | CLIMATE |
|--------------------------|--------------------------|--------------------------|
| Initial service | | Cold |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| SP Gear 1081 | SP Gear 5015 | SP Gear 1071 |

Change every 50 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.