MANITOU WHEELED LOADERS AL AL80



ENGINE Capacity: 10 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40	

DIFFERENTIAL FRONT LIMITED SLIP Capacity: 4,2 liter (20 km/h version), Capacity: 3,8 liter (30 km/h version)		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		
Check every 50 hours, change every 1500 h	ours	
USE	CLIMATE	
Initial service	Moderate	
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		
Change every 500 hours	<u>'</u>	

JSE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube LS 80W-90	
Check every 50 hours, change every 1500 hours	
JSE	CLIMATE
Initial service	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube LS 80W-90	

MANITOU WHEELED LOADERS AL AL80



HUB REDUCTIONS FRONT Capacity: 0,9 liter (each)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		
Check every 50 hours, change every 1500) hours	
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		
Change every 500 hours		
HUB REDUCTIONS REAR		
Capacity: 0,9 liter (each)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		
Check every 50 hours, change every 1500) hours	
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		
Change every 500 hours		
HYDRAULIC SYSTEM Capacity: 100 liter (Change capacity)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		

PRODUCT RECOMMENDATION T		
Perlus H 46		
Check every 10 hours, change every 1500) hours	
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
Perlus Biosynth 46		
Check every 10 hours, change every 1500) hours	
	l) hours	

MANITOU WHEELED LOADERS AL AL80



HYDRAULIC BRAKE SYSTEM	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Perlus H 46	
Check every 10 hours	

GREASE POINTS/NIPPLES	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
MoS2 Grease EP 2	
Check every 10 hours	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.