

MANITOU FORKLIFT TRUCKS M/MC M40-2T L PERKINS 1104D-44T TIER III (S/N 757730 - >)



ENGINE Perkins 1104D-44T
Capacity: 8,6 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel MSP 15W-40	Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40

Check every 10 hours, change every 500 hours/ 12 months

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak MTH 10W-30	Synfleet SHPD 10W-40	Armado Synth 5W-30

Check every 10 hours, change every 500 hours/ 12 months

DIFFERENTIAL FRONT Dana
Capacity: 6,8 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agrifluid HT-Plus	Agrifluid HT	

Check every 250 hours, change every 500 hours/ 12 months

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agrifluid HT-Plus	Agrifluid HT	

Change every 50 hours

HUB REDUCTIONS FRONT
Capacity: 0,76 liter (each hub)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 250 hours, change every 1000 hours/ 12 months

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Change every 50 hours

MANITOU FORKLIFT TRUCKS M/MC M40-2T L PERKINS 1104D-44T TIER III (S/N 757730 - >)



TRANSMISSION Turner 4/4 4/4
Capacity: 15,2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 2032

PRODUCT RECOMMENDATION 2

ATF Almirol

Check every 10 hours, change every 1000 hours/ 12 months

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 2032

PRODUCT RECOMMENDATION 2

ATF Almirol

Change every 50 hours

HYDRAULIC SYSTEM

Capacity: 98,4 liter (Hydraulic tank)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Perlus H 46

Check every 50 hours, change every 1000 hours/ 12 months

HYDRAULIC BRAKE SYSTEM

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 2032

PRODUCT RECOMMENDATION 2

ATF Almirol

Check every 50 hours, change every 1000 hours/ 12 months

GREASE POINTS/NIPPLES

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

MoS2 Grease EP 2

MANITOU FORKLIFT TRUCKS M/MC M40-2T L PERKINS 1104D-44T TIER III (S/N 757730 - >)

**COOLING SYSTEM**

Capacity: 18,9 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Check every 10 hours, change every 2000 hours/ 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.